×



Item Number EB15622768

https://www.eibabo.uk/hager/fire-protection-cabinet-universal-1498x398x349-30-min-distribution-cabinet-empty-1498x398mm...-eb15622768



Fire protection cabinet, universal 1498x398x349, 30 min - Distribution cabinet (empty) 1498x398mm...

Hager

FB91LE 3250616003651 EAN/GTIN

2072,60 GBP excl. VAT**

plus **shipping bulky item**



14-16 days* (GBR)

Fire protection cabinet, univ. 1498x398x349, 30 min FB91LE surface mounting type of cover, door design, closed cover, type of door single, with lock, rated current (In) 250A, height 1498mm, width 398mm, depth 349mm, inner depth 240mm, material thickness housing 70mm, Material thickness door/cover 22mm, color grey, RAL number 7035, number of modules 108, number of rows 9, width in modular units 1, number of openings for flange plates 2, number of cable entries 1, housing material plastic, surface painted, Degree of protection (IP) IP43, protection class II, impact resistance IK10, functional integrity E 30, fire protection cabinet, univers, 1498 x 398 x 349 mm, 30 minutes. Electric fire protection wall cabinet F30 for mounting on the wall to secure escape and rescue routes (fire load insulation), prepared for setting up a low-voltage distribution board up to 630A. Suitable for maintaining the functionality of safety systems in the event of a fire for more than 30 minutes. The housing is made of class A2 non-combustible building material? \$1, d0 manufactured, IP44, protection class II, color similar to RAL7035 and top/bottom cable entries. General technical approvals (DIBt): Z-86.1-86. Wall cabinet consisting of empty housing, fastening straps and fastening material. Door with one or two doors opening into the body with door hinges can be changed to the right or left, opening angle 180°. Door with swivel lever, door lock via push rod with 2-point locking and with DIN half cylinder double bit, interchangeable, door hinges made of stainless steel. Rear wall with active ventilation system 230V AC, cold smoke-tight, in the event of fire it switches itself off via smoke detectors and automatically foaming fire protection seal (all-round). The housing can be provided with different surfaces (decor/lacquer/veneer/metal) from the manufacturer.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

