

## Item Number EB16005560

https://www.eibabo.uk/hager/add-on-distributor-6-fields-distribution-cabinet-empty-1900x1600mm-fg26xd-eb16005560



## Add-on distributor 6 fields - Distribution cabinet (empty) 1900x1600mm FG26XD

## Hager

FG26XD 3250612794782 EAN/GTIN

1670,53 GBP excl. VAT\*\*

plus **shipping bulky item** 



14-16 days\* (GBR)

Modular distributor 6-field FG26XD Type of installation floor installation, type of cover door, design cover closed, type of door double, with lock, nominal current (In) 1600A, height 1900mm, width 1600mm, depth 600mm, installation depth 600mm, inner depth 600mm, material thickness housing 1.5mm, Material thickness of door/cover 1.5mm, color grey, RAL number 7035, number of modules 864, number of rows 72, width in modular units 72, number of openings for flange plates 12, mounting option, number of cable entries 12, housing material steel, Powder-coated surface, degree of protection (IP) IP54, protection class I, impact resistance IK10, functional integrity without, modular cabinet, univers, IP 54, protection class I, 1900x1600x600 mm. Bayed cabinet for indoor assembly according to VDE 0660 part 600-1/-2, DIN EN 61 439-1/-2, dimensions according to DIN 43870 protection class, IP 54 according to DIN EN60529 (VDE0470-1), protection class IP 3x with open door, air - and creepage distances according to VDE 0110, part 1 and 2/1.89, rated insulation voltage AC 800 V, overvoltage category IV, degree of pollution 3, insulation class II, protection class I grounded. Free-standing housing for single or row installation with removable rear and side panels, width 1 to 6 fields, 144 to 864 space units. Interior system can be installed for mains systems: 3 AC 50 Hz 230/400 V or 3 AC 50 Hz 400/690 V with a maximum feed current of 1600 A. Cabinet frame made of galvanized sheet steel, cover plate and rear panel made of hot-dip galvanized sheet steel. With horizontal support rail for stabilizing the DIN rail, coupling plates for fastening the DIN rail, prepared for univers N interior installation system. Busbar bushings can be flanged next to one another through open side walls. Sheet steel door, powder-coated and stoved, surface-mounted with internal hinges, can be attached on the right or left. Door opening angle 120°, from a width of 1100 mm double door, door lock with standard built-in four-point bar lock (knodors) with 3 mm

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING** *Obliging and 100% safely* 



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

