

Item Number EB11607289

https://www.eibabo.uk/schneider-electric/safety-relay-3s-1t-24v-sk-safety-relay-24v-ac-dc-en954-1-cat-4-xpsuaf13ap-eb11607289



Safety relay 3S 1T 24V SK - Safety relay 24V AC/DC EN954-1 Cat 4 XPSUAF13AP

×

Schneider Electric XPSUAF13AP 3606489601614 EAN/GTIN

97,99 GBP excl. VAT**

plus **shipping**



3-5 days* (GBR)

Safety relay 3S 1T 24V SK XPSUAF13AP Basic device version, Suitable for monitoring position switches, Suitable for monitoring EMERGENCY STOP circuits, Suitable for monitoring optoelectronic protective devices, Suitable for monitoring magnetic switches, Suitable for monitoring proximity switches, Design of the electrical connection screw connection, DIN rail mounting possible, Rated control supply voltage Us at AC 50 Hz 24 ... 24V, Rated control supply voltage Us at AC 60 Hz 24 ... 24V, Rated control supply voltage Us at DC 24 ... 24V, Type of voltage for actuation AC/DC, With removable terminals, Evaluation of Two-channel inputs, with start input, with feedback loop, off-delay 0s, number of outputs, safety-related, instantaneous, contact-based 3, number of outputs, safety-related, delayed, contact-based 0, number of outputs, signaling function, instantaneous, semiconductor 0, number of outputs, safety-related , delayed, semiconductor 0, number of outputs, signaling function, delayed, contact-based 0, number of outputs, signaling function, instantaneous, semiconductor 0, category according to EN 954-1 4, safety type according to IEC 61496-1 4, stop category according to IEC 60204 0, performance level according to EN ISO 13849-1 Level e, SIL according to IEC 61508 3, with TÜV approval, with UL approval, width 22 ,5mm, height 100mm, depth 120mm, safety relay Preventa XPS Universal. Multifunctional safety relay for a wide range of safety applications thanks to a selectable safety function and start option using a rotary switch on the front, as well as diagnostic communication with the PLC. Suitable for mechanical contacts in emergency stop/stop, position or magnetic switches, as well as electronic PNP sensors, light curtains or RFID safety function 1 from 6. Outputs safe relay 3S - diagnosis 1T. Clocked output transmits comprehensive diagnostic data to the PLC at the standard input and evaluation via FB. Safety level PL e, cat. 4, SIL3. Supply voltage 24 VAC/DC. Connections removable screw terminals. Lateral connec

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

