



**LED floodlight incl. 3m cable - Downlight/spot/floodlight  
MT69071**



IDV

MT69071

4020856690718 EAN/GTIN

**23,00 GBP** excl. VAT\*\*  
plus shipping



14-16 days\* (GBR)

Energy efficiency classes spectrum A to G, Suitable for wall mounting no, Suitable for recessed mounting no, Suitable for surface mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting yes, Suitable for truss mounting yes, Suitable for pedestal / floor mounting yes, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability swiveling, With motion detector no, With light sensor no, Lamp LED not interchangeable, With bulbs yes, Version without, Material of the housing Aluminum, Surface protection other, Housing Color black, Material of the cover Glass structured, Surface brushed no, Voltage AC, Nominal voltage 220..240 V, Control gear not mandatory, With operating device yes, Replaceable operating device no, Dimming dependent on control gear no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI-2 no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific yes, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function no, Reflector white, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light output directly, Constant luminous flux control no, IP protection) IP65, Protection class I, Max. System performance 10W, Light color RGBW, Color temperature 3000K, Color rendering index CRI 80-89, Luminous flux 900 lm, Rated luminous flux according to IEC 62722-2-1 900 lm, Power factor 0.5, Colour temperature adjustable no, Light current adjustable Stages, Beam angle adjustable no, Width 138 mm, Height / depth 110 mm, Length 25 mm, Type of wiring graduation, Number of poles 3, Connection Plug-in terminal, Integrated emergency power supply no, luminous efficacy 90 lm/W, IFTTT support available no, Colour consistency (McAdam ellipse) SDCM3, Compatible with Apple HomeKit no, Compatible with Google Assistant no, Compatible with Amazon Alexa no

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**

Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**

> 500,000 customers worldwide



**DHL TRACK & TRACE**

Shipment tracking



**COMPLAINTS HANDLING**

Obliging and 100% safely



**25 YEARS OF EXPERIENCE**

In worldwide mail order



**ORDER LIVE CHAT**

With order history



**SHORT DELIVERY TIME**

Warehousing



**REFUND**

Within 14 days



**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

