

Item Number EB13909327

25.04.2024/08:48

×

https://www.eibabo.uk/eaton/power-contactor-3-pole-magnet-contactor-150a-190...240vac-0vdc-dilmc1 50-rac240-eb13909327



Power contactor 3-pole - Magnet contactor 150A 190...240VAC 0VDC DILMC150(RAC240)

Eaton DILMC150(RAC240) 239751 4015082397517 EAN/GTIN

459,95 GBP excl. VAT**

plus shipping



Power contactor 3-pole DILMC150(RAC240) Rated control supply voltage Us at AC 50 Hz 190 ... 240V, Rated control supply voltage Us at AC 60 Hz 190 ... 240V, Rated control supply voltage Us at DC 0V, Type of voltage for actuation AC, Rated operational current le at AC-1, 400 V 190A, Rated operational current le at AC-3, 400 V 75kW, rated operational current le at AC-4, 400 V 65A, rated operational power at AC-4, 400 V 03kW, rated operational power NEMA 93kW, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NO contact 0, number of auxiliary contacts as NO contacts on power contactors up to 170 A, 3-pole, utilization category: AC-1: Non-inductive or weakly inductive load, resistance furnaces, AC-3: squirrel-cage motors: starting, switching off during run, AC-4: squirrel-cage motors: starting, counter current braking, reversing, jogging, Connection technology: Spring-loaded terminals, Note: Also suitable for motors, Poles: 3-pin , Rated operational current AC-3 at00 V : le = 150 A, Rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: Ith = le= 190 A, encapsulated: Ith= 144 A, Rated operational current AC-1 conventional thermal current 3-pole, 50 - 60 Hz open at 40 °C: Ith = le= 190 A, encapsulated: Ith= 144 A, Rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: Ith = le= 190 A, encapsulated: Ith= 144 A, Rated operational current AC-1 conventional thermal current, 3-pole, 50 - 60 Hz open at 40 °C: Ith = le= 190 A, encapsulated: Ith= 144 A, Rated operational current AC-3 220 V 230 V: P= 48 kW, 380 V 400 V : P= 75 kW, 660 V 690 V: P= 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V: P= 33 kW, 660 V 690 V: P= 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V: P= 33 kW, 660 V 690 V: P= 96 kW, max. rated operational power of three-phase motors 50 - 60 Hz AC-4 220 V 230 V: P= 20 kW, 380 V 400 V

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

