

LED tube light 1.6m 4000K DV3x1.5 - Ceiling-/wall luminaire TUBIS BL #5240035



Pracht
TUBIS BL #5240035
5240035
4018098361718 EAN/GTIN



66,25 GBP excl. VAT**
plus shipping bulky item



3-5 days* (GBR)

LED tube light 1.6m 4000K DV3x1.5 TUBIS BL 5240035 Suitable for wall mounting, Suitable for pendulum suspension, Suitable for ceiling mounting, Light source LED not replaceable, With light source, Suitable for number of light sources 1, Other socket, Material of the housing plastic, Housing color other, Material of the cover plastic opal, design of the louvre without, type of voltage AC/DC, nominal voltage 220 ... 240V, nominal LED current at constant current 300 ... 300mA, control gear LED control gear current-controlled, with control gear, without dimming function, light distributor diffuser lens/- Optics/panel, symmetrical light distribution, extremely wide beam angle >80°, direct light emission, energy efficiency index (EEI) of the power supply other, rated service life L70/B10 at 25 °C 100,000 h, rated service life L70/B50 at 25 °C 100,000 h, rated service life L80/B10 at 25 °C 92000h, rated service life L80/B50 at 25 °C 100000h, rated service life L90/B10 at 25 °C 44000h, Be Measurement service life L90/B50 at 25 °C 49000h, degree of protection (IP) IP69K, degree of protection (NEMA) other, impact resistance IK06, protection class I, luminaire with limited surface temperature "D mark", rated ambient temperature according to IEC62722-2-1 -20 ... 40°C, glow wire test according to IEC 60695-2-11 650 °C - 30 s, max. system power 42W, rated luminous flux according to IEC 62722-2-1 6500lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80- 89, light output 155lm/W, power factor 0.93, width 81mm, height/depth 80mm, length 1629mm, outer diameter 70mm, type of wiring with through-wiring, number of poles 3, conductor cross-section 1.5mm², connection type plug-in terminal, LED tube light with ø70mm round tube housing made of co -extruded PMMA blend (impact resistant IK06) with extremely short sealing paths made of silicone and welded end caps. Including 3x1.5mm² through-wiring ex works. Quick and easy installation thanks to simplified cable connection and stainless steel clamps, suitable for ceilings, horizontal and vertical wall mounting, pendant and mounting rail mounting with accessories possible. Suitable for unprotected outdoor areas and approved for unrestricted animal husbandry.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

