×



https://www.eibabo.uk/siemens/circuit-breaker-3va5-ul-frame-125-3va5130-4ed11-0aa0-eb17022292



Circuit breaker 3VA5 UL Frame 125 3VA5130-4ED11-0AA0

Siemens

3VA5130-4ED11-0AA0 4042948838495 EAN/GTIN

86,06 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Circuit breaker 3VA5 UL Frame 125 3VA5130-4ED11-0AA0 Rated uninterrupted current lu 30A, rated voltage 415... 415V, rated limiting short-circuit breaking current lcu at 400 V, 50 Hz 5kA, overload release current setting 30... 30A, setting range of the instantaneous short-circuit release 300... 300A, connection type Other main circuit, device design built-in device fixed installation technology, suitable for top hat rail mounting, top hat rail mounting optional, number of auxiliary contacts as opener 0, number of auxiliary contacts as make contact 0, number of auxiliary contacts as changeover contact 0, number of poles 1, position of the connection for main circuit other, design of the actuating element rocker arm, Complete device with protection unit, degree of protection (IP) IP40, circuit breaker 3VA5 UL Frame 125 switching capacity class S 25kA @ 277V 1-pole, system protection TM210, FTFM, In=30A overload protection Ir=30A fixed short-circuit protection Ii=10 x In without connection 3VA5 molded case circuit breakers for system protection , UL approval. The 3VA UL molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective system and starter protection through safe shutdown in the event of an overload or short circuit. The 3VA UL sets standards in terms of flexibility and modular variety of accessories. The 3VA UL molded case circuit breakers also offer the best conditions for machines and switchgear manufacturers exporting worldwide. In addition to the IEC standard, the two series 3VA5 and 3VA6 also meet the UL standard. All functionalities can thus be used and used worldwide for systems. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1. Compact design. 2. Available as a variant for system protection. 3. Depending on the size: 1-, 2- (3-pole housing design) and 3-pole versions. 4. Depending on size: switching capacity of 25kA. 100 kA at 48

YOUR ADVANTAGES



WORLDWIDE TRADECorporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE *In worldwide mail order*



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTIONGuarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

