



**OELFLEX CLASSIC 110 3x1.5 - Power cable < 1kV,  
moving inst. 3x1,5mm<sup>2</sup> 1119903 R100**



**Lappkabel**  
1119903 R100  
1119903/100  
4044774557663 EAN/GTIN

**76,98 GBP** excl. VAT\*\*  
plus shipping bulky item

 **14-16 days\* (GBR)**

ÖLFLEX CLASSIC 110 3x1.5 1119903 R100 Nominal conductor cross-section 1.5mm<sup>2</sup>, conductor class class 5 = finely stranded, number of cores 3, stranding element no, material of core insulation polyvinyl chloride (PVC), core identification numbers, screen over stranding element without, Shield over stranding without, sheath material polyvinyl chloride (PVC), sheath color gray, fire behavior class according to EN 13501-6 Eca, flame-retardant according to EN 60332-1-2, outer diameter approx. 6.7mm, max. Cable outside temperature during assembly/handling -15 ... 70°C, perm. Cable outside temperature after installation without vibration -40 ... 80°C, rated voltage U0 300V, rated voltage U 500V, number of protective conductors 0, fixed installation as well as occasional flexible use without tensile stress with free, not constantly recurring movement, dry or damp rooms normal mechanical stress, Suitable for torsion applications that are typical in the loop of wind turbines (WKA), In cable drag chains for travel distances of up to 5 m and 0.2 ... 1 million bending cycles, for the following dimensions: 0.5 to 2.5 mm<sup>2</sup> and 2 to 7 cores, Large range of standardized lengths and individual cuts, Very large range of articles, Designs with up to 100 cores, Fine-wire strands made of bare copper wires, PVC core insulation LAPP P8/1, cores stranded in layers, PVC sheath, gray (RAL 7001), VDE reg. no. 7030 for the following dimensions: up to 2.5 mm<sup>2</sup>: 2 - 65 cores from 4 mm<sup>2</sup>: 2 - 7 cores from 25 mm<sup>2</sup>: 2 - 5 cores, flame-retardant according to IEC 60332-1-2, good chemical resistance, oil-resistant according to DIN EN 50290 -2-22 (TM54)

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

