

Item Number EB16322241

×

https://www.eibabo.uk/sick/diffuse-mode-sensor-pnp-npn-switchable-background-masking-photoelectri c-sensor-wt24-2b240s13-eb16322241



## Diffuse mode sensor PNP/NPN, switchable - Background masking photoelectric sensor WT24-2B240S13

Sick WT24-2B240S13 1022293 4047084125614 EAN/GTIN

## 359,50 GBP excl. VAT\*\*

plus shipping



Adjustment 100..1200 mm, Operating distance 100..1200 mm, Triangulation Background suppression, Failure warning no, With time function no, Rated operating distance 1200 mm, Max. Output current 100mA, With reflector no, Analog output 0 V ... 10 V no, Analog output 0 mA ... 20 mA no, Analog output 4 mA ... 20 mA no, Analog output -10 V ... +10 V no, With other analog output no, Adjustment manual adjustment, With communication interface analog no, With communication interface AS-Interface no, With communication interface CANOpen no, With communication interface BeviceNet no, With communication interface Ethernet no, With communication interface RS-100, With communication interface RS-232 no, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-232 no, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-232 no, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, With communication interface RS-422 no, With communication interface RS-00, No, Operating resource protection class Protection class 2, Explosion protection category for gas without, Explosion protection category for dust without, Housing Construction Cuboid, Width of the sensor 27 mm, Height of the sensor 87.5 mm, Length of the sensor 65 mm, Key functio

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

