



**LED wall light Up/Down - Ceiling-/wall luminaire 1x7W  
ALVAUDLTR281100840AN**



**ESYLUX**  
ALVAUDLTR281100840AN  
EL10830068  
4015120830068 EAN/GTIN

**172,61 GBP** excl. VAT\*\*  
plus shipping

 14-16 days\* (GBR)

Ceiling-/wall luminaire 1x7W, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for recessed mounting no, Suitable for surface mounting yes, Illuminant LED not interchangeable, With illuminants yes, Suitable for light band configuration no, Suitable for number of lamps 1, Lamp holder other, Material of the housing Aluminum, Housing color gray, Material of the cover Plastic transparent, Type of grid without, Voltage AC, Rated voltage 230V, Operating device LED operating device current-controlled, With operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function yes, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle medium-emitting 21-40°, Light outlet direct / indirect, Rated service life L70/B10 at 25 °C 125000 h, Rated service life L70/B50 at 25 °C 225000 h, Rated service life L80/B10 at 25 °C 80000 h, Rated service life L80/B50 at 25 °C 140000 h, Rated service life L90/B10 at 25 °C 40000 h, Rated service life L90/B50 at 25 °C 70000 h, Degree of protection (IP) IP65, Impact resistance IK09, Protection class I, Suitable for emergency light no, With motion detector no, With light sensor no, With louvers no, Suitable for lamp power 7 W, Max. System performance 10W, Rated luminous flux according to IEC 62722-2-1 1050 lm, Light color white, Color temperature 4000K, Color rendering index CRI 80-89, luminous efficacy 105 lm/W, Width 100 mm, Height/depth 160 mm, Length 176 mm, Outer diameter 160 mm, Number of poles 3, Conductor cross-section 2.5 mm², Connection type Plug-in terminal

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt<sup>®</sup>



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo<sup>®</sup>** and **eibmarkt<sup>®</sup>** are registered trademarks of EIBMARKT<sup>®</sup> GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo<sup>®</sup> is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT<sup>®</sup> GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo<sup>®</sup>** the Smart Home technology shop  
**eibabo<sup>®</sup>** electronics cheap online order  
**eibabo<sup>®</sup>** electric appliances buy online

