

Item Number EB16218290

https://www.eibabo.uk/siemens/sirius-soft-starter-200-690-v-1280-a-soft-starter-1280a-110...250vac-3r w55582ha16-eb16218290



SIRIUS soft starter 200-690 V 1280 A - Soft starter 1280A 110...250VAC 3RW55582HA16

Siemens

3RW55582HA16 4047621059457 EAN/GTIN

17583,16 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

SIRIUS soft starter 200-690 V 1280 A 3RW55582HA16 Rated operating current le at 40 °C Tu 1280A, rated operating voltage Ue 200 ... 690V, rated power three-phase motor, standard circuit, at 230 V 400kW, rated power three-phase motor, standard circuit, at 400 V 710kW, rated power three-phase motor, root -3 circuit, at 230 V 710kW, rated power three-phase motor, root 3 circuit, at 400 V 1200kW, function in one direction of rotation, internal bridging, with display, torque control, rated ambient temperature without derating 40°C, rated control supply voltage Us at AC 50 Hz 110 ... 250V, rated control supply voltage Us at AC 60 Hz 110 ... 250V, voltage type for actuation AC, integrated overload protection of the motor, tripping class adjustable, protection class (IP) IP00, SIRIUS soft starter 200-690 V 1280 A, AC 110- 250 V spring-loaded terminals SIRIUS 3RW55 High Performance soft starter for demanding applications for the gentle starting and stopping of three-phase asynchronous motors. Continuously variable starting, reducing current peaks, avoiding mains voltage fluctuations during startup, relieving the load on the power supply network, reducing the mechanical load on the drive, significant space and wiring savings compared to star-delta starters and frequency converters, maintenance-free switching and extremely easy handling. The integrated bypass enables the very compact design, saves energy and ensures less heating in the control cabinet. Intelligent monitoring functions protect the soft starter from overheating and the motor from overload. You can also limit the current to an adjustable maximum value during startup. Thanks to the 3-phase control, it is particularly suitable for large motor outputs and root-3 circuits. The innovative torque control ensures optimal engine startup. Simple and quick commissioning through auto-parameterization or application assistant. Predictive maintenance planning through condition monitoring. Removable HMI with color display for clear measured value and diagnostic displays. Worldwide approvals (e.g. IEC and UL/CSA). The 3RW55 high-performance soft starters are available for networks up to 690 V in a power range of up to 560 kW with 24 V or 110-250 V control supply voltages and consistently with screw and spring-loaded connections. Analog output and thermistor motor protection are an integral part of the high performance soft starters. Optional plug-in communication modules enable connection via PROFINET, PROFIBUS and Modbus TCP. The built-in HMI module can also be mounted in the control cabinet door. The 3RW55 soft starters replace the proven 3RW44 series. SIRIUS 3RW5 soft starter - as flexible as your...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

**** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

