



Circuit breaker 3VA1 IEC frame 160 3VA1108-5MG32-0AA0



Siemens
3VA1108-5MG32-0AA0
4042948828533 EAN/GTIN

191,09 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

Circuit breaker 3VA1 IEC Frame 160 3VA1108-5MG32-0AA0 Rated continuous current I_n 8A, rated voltage 690... 690V, rated limiting short-circuit breaking current I_{cu} at 400 V, 50 Hz 55kA, setting range of the instantaneous short-circuit release 128... 128A, connection type main circuit screw connection, device type built-in device fixed installation technology, suitable for top-hat rail mounting, top-hat rail mounting optional, number of auxiliary contacts as opener 0, number of auxiliary contacts as make contact 0, number of auxiliary contacts as changeover contact 0, number of poles 3, position of the connection for the main circuit at the front, design of the actuating element toggle, complete device with protective unit, motor drive optional, degree of protection (IP) IP40, circuit breaker 3VA1 IEC frame 160 switching capacity class M I_{cu}=55kA @ 415V 3-pole, starter protection TM110M, FM, I_n=8A without overload protection, short-circuit protection I_Δ=15 x I_n screw flat connection 3VA1 molded case circuit breaker for starter protection. The 3VA molded case circuit breakers from Siemens, as an important part of the SENTRON protective components for industrial applications and for applications in the infrastructure sector, offer effective system, starter and motor protection through safe disconnection in the event of an overload or short circuit. The 3VA molded case circuit breakers set standards in terms of flexibility and modular variety of accessories. Uniform accessories for several sizes across all series of 3VA1 and 3VA2 molded case circuit breakers. This variant of the 3VA molded case circuit breaker is primarily characterized by: 1. Compact design. 2. Available as a variant for starter protection to protect electric motors against short circuits. 3. Available in 3 pole version. 4. Depending on the size: Rated operational current of 1 A... 200 A. 5. Switching capacity of 55 kA... 70 kA at 415 V. 6. Fixed installation and plug-in technology possible. 7. The range has a thermal-magnetic overcurrent release 8. Modular and easy to assemble internal accessories with multiple functions. 9. Consistent accessory platform for all 3VA molded case circuit breakers. Siemens offers an integrated portfolio of protection, switching, measuring and monitoring devices, distribution systems, switches and sockets for safe, efficient electrical infrastructure in buildings and industry.

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

