

Item Number EB17002615

https://www.eibabo.uk/trilux/led-moisture-proof-luminaire-b-4000-840et-hfs-ceiling-wall-luminaire-nextrema-q3-6628340-eb17002615



LED moisture-proof luminaire B 4000-840ET+HFS - Ceiling-/wall luminaire Nextrema G3 #6628340

×

Trilux

Nextrema G3 #6628340 6628340 4018242346578 EAN/GTIN

226,01 GBP excl. VAT**

plus shipping



14-16 days* (GBR)

LED moisture-proof luminaire B 4000-840ET+HFS Nextrema G3 6628340 Suitable for wall mounting, Suitable for pendant suspension, Suitable for ceiling mounting, Suitable for surface mounting, Light source LED not replaceable, With light source, Suitable for number of light sources 1, Other socket, Housing material aluminium, Housing color anthracite, cover material structured plastic, design of the louvre without, voltage type AC/DC, nominal voltage 230 ... 230V, control gear electronic transformer, with control gear, without dimming function, other light distributor, symmetrical light distribution, direct light emission, energy efficiency index (EEI) of Other power supply, Protection class (IP) IP66, Protection class (NEMA) other, Impact resistance IK04, Protection class I, Luminaire with limited surface temperature "D mark", Rated ambient temperature according to IEC62722-2-1 -30 ... 35°C, With Motion detector, with light sensor, the lamp can be covered with thermal insulation material, glow wire test according to IEC 60 695-2-11 650 °C - 30 s, max. system power 32W, rated luminous flux according to IEC 62722-2-1 4500lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, luminous efficacy of luminaire 140lm/W, width 96mm, height/depth 98mm, length 1047mm, type of wiring termination, number of poles 3, connection type plug-in terminal, LED moisture-proof light. Luminaire in PMMA version suitable for use in uncovered outdoor areas due to the higher UV resistance. Complies with DIN 10500. The luminaires are suitable for use in HACCP, IFS Version 6 and/or BRC Global Standard Food Version 7 certified companies in the food and beverage industry. Luminaire with limited surface temperature according to DIN EN 60598-2-24 suitable for use in premises at risk of fire. For ceiling, wall and suspended mounting. Mounting clips and triangle brackets for suspended mounting included. Suitable for mounting on DIN rail 190 VZ. In the case of wall mounting, the lamp must be protected against unintentional dismantling by means of accessories to be ordered separately (eg ATL1). Wall mounting can be horizontal or vertical. PMMA diffuser with internal prism structure. With symmetric wide light intensity distribution. Glare rating according to UGR classification (EN 12464-1) < 25. Rated luminous flux 4500 lm, rated power 32.00 W, luminous efficacy of luminaire 141 lm/W. Light color neutral white, correlated color temperature (CCT) 4000 K, color location tolerance (initial MacAdam) 3 SDCM, general color rendering index (CRI) Ra > 80. Average rated service life L85(tq 35 °C) = 50,000 h, average rated...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

