



## LED mast/top light 3000K DALI anthr. - Luminaire for streets and places 612181.0031.76


**RZB**

612181.0031.76

4051859366751 EAN/GTIN

**404,13 GBP** excl. VAT\*\*

plus shipping



14-16 days\* (GBR)

LED mast/top light 3000K DALI anthr. 612181.0031.76 Type of mounting top/side attachment, Illuminant LED not replaceable, With illuminant, Suitable for number of illuminants 1, Socket without, Housing material aluminium, Surface powder-coated, Housing color anthracite, Cover material transparent glass, Type of voltage AC, Rated voltage 220 ... 240V, Control gear LED control gear, current-controlled, With control gear, Dimming DALI, Rated service life L80/B50 at 25 °C 100000h, Degree of protection (IP) IP66, Degree of protection (NEMA) other, Light distributor without, Suitable for spigot size 76 ... 76mm, Impact resistance IK08, Protection class II, rated ambient temperature according to IEC62722-2-1 -20 ... 50°C, remote control without, with connection cable, suitable for lamp power 97 ... 97W, max. system power 51W, rated luminous flux according to IEC 62722-2-1 8000lm, light colour white, color temperature 3000 ... 3000K, color rendering index CRI 70-79, luminous efficacy of luminaire 157lm/W, power factor 0.99, width 340mm, height/depth 100mm, length 700mm, type of wiring termination, 4 poles, conductor cross-section 2.5mm², connection type screw terminal, mounting on the mast as a mast attachment, or mast-top luminaire. Adjustable and lockable in 5° increments: Top mount: tiltable from -5° to +15° (straight masts). Extension mounting: tiltable from 0° to -30° (whip masts). Three spigot diameters are available for mounting on the mast (42 mm and 76 mm, 60 mm with reducer). CityTouch Ready, lights can be equipped with CityTouch components if required. The comprehensive selection of light distributions and light outputs enables universal use in the lighting of private paths, public streets and area lighting (parking lots) in accordance with DIN EN 13201. Plug + play concept for simple and safe installation: thanks to the factory-fitted 8 m connection cable, the Luminaire required for installation. Mains interruption when opening the housing. Tool-free maintenance/replacement thanks to Eccentric-Lock-System and Hybrid-Lock-System. Seawater resistant coating. Ballast with integrated overvoltage protection. LED service life 64,000 h (L80, B10). Operating range -20°C to +40°C. Housing made of corrosion-resistant die-cast aluminium, seawater-resistant powder-coated. Pole top with integrated cable routing and stainless steel screws. Cover tempered safety glass (ESG), clear, edge printed. Tool-free maintenance/replacement thanks to Eccentric, Lock, system with disconnect plug and Hybrid, Lock, system. Asymmetrical light distribution optimized for area lighting (P and C lighting classes). Complete with connecting cable...

### YOUR ADVANTAGES


**WORLDWIDE TRADE**

Corporate video eibmarkt®


**99% CUSTOMER SATISFACTION**

&gt; 500,000 customers worldwide


**DHL TRACK & TRACE**

Shipment tracking


**COMPLAINTS HANDLING**

Obliging and 100% safely


**25 YEARS OF EXPERIENCE**

In worldwide mail order


**ORDER LIVE CHAT**

With order history


**SHORT DELIVERY TIME**

Warehousing


**REFUND**

Within 14 days


**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

