



**Sensor LED spotlight IP44, BMW, ws -
Downlight/spot/floodlight XLED ONE Sensor weiß**



Steinel
XLED ONE Sensor weiß
065256
4007841065256 EAN/GTIN

62,60 GBP excl. VAT**
plus shipping

 14-16 days* (GBR)

Downlight/spot/floodlight, Suitable for surface mounting yes, Suitable for recessed mounting no, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting yes, Suitable for truss mounting no, Suitable for pedestal/floor mounting yes, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability swiveling, With motion detector yes, With light sensor yes, Illuminant LED not interchangeable, With illuminants yes, Lamp holder other, Material of the housing Aluminum, Housing color white, Material of the cover Glass transparent, Surface brushed no, Voltage AC, Rated voltage 220..240 V, With operating device yes, Dimming dependent on control gear no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Potentiometer (device-integrated) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, Reflector white, light distributor without, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light outlet directly, Degree of protection (IP) IP44, Protection class I, Suitable for lamp power 23.5 W, Max. System performance 23.5 W, Light color white, Color temperature 3000K, Color rendering index CRI 80-89, Luminous flux 2550 lm, Rated luminous flux according to IEC 62722-2-1 2550 lm, Lamp light output 108.511 lm/W, Width 229 mm, Height/depth 195 mm, Length 202 mm, Connection type other, luminous efficacy 108.511 lm/W, Photobiological safety according to EN 62471 RG1, Colour consistency (McAdam ellipse) SDCM3

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

