

## Item Number EB16218067

https://www.eibabo.uk/siemens/sirius-soft-starter-200-480-v-143-a-soft-starter-143a-24vac-24vdc-3rw5 0556tb04-eb16218067



# SIRIUS soft starter 200-480 V 143 A - Soft starter 143A 24VAC 24VDC 3RW50556TB04

×

#### Siemens

3RW50556TB04 4047621060279 EAN/GTIN

### 1585,17 GBP excl. VAT\*\*

plus **shipping** 



14-16 days\* (GBR)

SIRIUS soft starter 200-480 V 143 A 3RW50556TB04 rated operational current le at 40 °C Tu 143 A, rated operational voltage Ue 200 ... 480 V, rated power three-phase motor, standard circuit, at 230 V 37 kW, rated power three-phase motor, standard circuit, at 400 V 75 kW, function one direction of rotation, Internal bypass, rated ambient temperature without derating 40°C, rated control supply voltage Us at AC 50 Hz 24 ... 24V, type of voltage for actuation AC/DC, Integrated motor overload protection, adjustable tripping class, degree of protection (IP) IP00, SIRIUS soft starter 200-480 V 143 A, AC/DC 24 V screw terminals, thermistor input SIRIUS 3RW50 Basic Performance soft starter for simple applications for smooth starting and stopping of three-phase asynchronous motors. Infinitely variable Starting, reducing current peaks, avoiding mains voltage fluctuations during start-up, relieving the load on the om supply network, reduction of the mechanical load in the drive, significant space and wiring savings compared to star-delta starters and frequency converters, maintenance-free switching and extremely simple handling. The integrated bypass enables the very compact design, saves energy and ensures less heating in the control cabinet. Intelligent monitoring functions protect the soft starter from overheating and the motor from overload. In addition, you can limit the current during startup to an adjustable maximum value. The innovative Soft-Torque function ensures that the motor starts up gently. With the integrated remote reset, you can quickly and easily fix faults remotely. Worldwide approvals (eg IEC and UL/CSA) also for potentially explosive applications (ATEX or IEC Ex). The Basic Performance 3RW50 soft starters are available for mains up to 600 V in a power range up to 315 kW with 24 V or 110-250 V control supply voltages and consistently with screw and spring-type terminals. Different device variants are available for installation in the control cabinet door. The 3RW50 soft starters replace the tried-and-te

#### YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION





25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for delivery

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

