

**LED gear tray 4000K - Gear tray for light-line system  
VLGFL1501-5 #1551330**



**Ridi-Leuchten**  
VLGFL1501-5 #1551330  
1551330  
4029299542103 EAN/GTIN



**117,08 GBP** excl. VAT\*\*  
plus shipping bulky item



3-5 days\* (GBR)

LED gear tray 4000K VLGFL1501-5 1551330 Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Housing material aluminium, Housing color white, Type of voltage AC, Nominal voltage 220 ... 240V, Control gear electronic ballast, With control gear, Without dimming function, Reflector without, symmetrical light distribution, direct light emission, degree of protection (IP) IP54, protection class I, max. system power 47W, rated luminous flux according to IEC 62722-2-1 8300lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, width 67mm, height/depth 66mm, length 1500mm, luminous flux can be switched in steps, LED gear tray made of extruded aluminum profile, white (...WS-...), silver (...SI-...) or black (...SW-...) powder-coated. RIDI LED linear modules equipped with mid-power LEDs for maximum efficiency. The circuit boards are pressed onto the aluminum profile over their entire surface for optimal heat dissipation. Solder joints of the LED modules tested according to the strictest quality standard with regard to formation of cavities and stability with vibration and torsion. No thermal coupling between LED modules and converter. Lens optics with wide-angle light distribution made of clear, UV-resistant PMMA, integrated flush in the gear tray. Thermoplastic end caps. Width of the gear tray identical to the mounting rail. Spring steel clip for fastening the gear tray in the VLTM trunking. Together with the VLTM trunking for the production of modular and variable light strips with protection class IP20 and IP50. The gear trays can be mounted anywhere on the trunking. Electrical adapter for flexible tapping of the power supply in the DIN rail with automatically contacted protective conductor. Phase selection by sliding contact. Color and optical coding for easy assembly. Mechanical coding to avoid incorrect assembly (twist protection). In the case of variably placed gear trays and when the control gear meets the trunking rail connector, installation is only possible with the trunking rail connector VLTV ...-600. The luminous flux can be adjusted via the 10 different levels of the ResFlex.

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
*Corporate video eibmarkt®*



**99% CUSTOMER SATISFACTION**  
*> 500,000 customers worldwide*



**DHL TRACK & TRACE**  
*Shipment tracking*



**COMPLAINTS HANDLING**  
*Obliging and 100% safely*



**25 YEARS OF EXPERIENCE**  
*In worldwide mail order*



**ORDER LIVE CHAT**  
*With order history*



**SHORT DELIVERY TIME**  
*Warehousing*



**REFUND**  
*Within 14 days*



**DATA PROTECTION**  
*Guarantee*

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

