



LED wall light BWM 3000K - Ceiling-/wall luminaire 1x8,6W 621090.0031.19



RZB
621090.0031.19
4051859185352 EAN/GTIN

294,76 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

LED wall light BWM 3000K 621090.0031.19 Suitable for wall mounting, Suitable for surface mounting, LED illuminant cannot be replaced, With illuminant, Suitable for computer workstations according to EN 12464-1, Suitable for number of illuminants 1, Other socket, Housing material aluminium, Housing color anthracite, Cover material Opal glass, design of the louvre without, type of voltage AC, nominal voltage 220 ... 240V, no operating device required, without dimming function, light distributor without, light distribution symmetrical, beam angle unshielded/diffuse, light emission direct/indirect, protection class (IP) IP54, protection class (NEMA) other, impact resistance IK02, protection class I, rated ambient temperature according to IEC62722-2-1 -20 ... 35°C, with motion detector, with light sensor, glow wire test according to IEC 60695-2-11 650 °C - 30 s, suitable for lamp power 8 ,6 ... 8.6W, max Performance index CRI 80-89, luminous efficacy of luminaire 70lm/W, width 156mm, height/depth 530mm, length 250mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in terminal, wall lights in classic design language. Opal glass for a glare-free appearance. Resistant plastic cylinders made of UV-stabilized polyethylene also allow use in an environment with increased mechanical loads. High-quality materials glass, aluminum and stainless steel for a long service life. Different equipment variants for optimal and energy-saving operation. Wall bracket in die-cast aluminium, powder-coated. Diffuser glass opal satin finish, hand-blown. The cover is fastened with a bayonet catch. Wall arm with motion detector including twilight switch. Mounting height of the wall light 2.0 m to 2.5 m. Maximum switching capacity 1000 W (resistive load), switch-on time adjustable from 6 seconds to 8 minutes, twilight value adjustable from 5 lux to 2000 lux, horizontal detection angle 360°, vertical 25°, detection range 9 m

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

