

Item Number EB13244240

×

https://www.eibabo.uk/esylux/led-spotlight-with-bwm-4000k-white-downlight-spot-floodlight-1x50w-basi cafitr5000840mdw-eb13244240



## LED spotlight with BWM 4000K white -Downlight/spot/floodlight 1x50W BASICAFLTR5000840MDW

ESYLUX BASICAFLTR5000840MDW EL10810763 4015120810763 EAN/GTIN



plus shipping



Downlight/spot/floodlight 1x50W, Suitable for surface mounting yes, Suitable for recessed mounting no, Suitable for wall mounting yes, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for truss mounting no, Suitable for pedestal/floor mounting no, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability swiveling, With motion detector yes, With light sensor yes, Illuminant LED not interchangeable, With illuminants yes, Suitable for number of lamps 1, Lamp holder without, Material of the housing Aluminum, Surface powder-coated, Housing color white, Material of the cover Glass transparent, Surface brushed no, Voltage AC, Rated voltage 220..240 V, LED rated current at constant current 208..227 mA, Operating device LED operating device current-controlled, With operating device yes, Dimming dependent on control gear no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, Reflector white, light distributor Reflector, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light outlet directly, Energy efficiency index (EEI) of the power supply system a2, Rated service life L70/B10 at 25 °C 50000 h, Rated service life L90/B10 at 25 °C 35000 h, Rated service life L90/B10 at 25 °C 35000 h, Rated service life L90/B10 at 25 °C 25,000 h, Rated service life L90/B50 at 25 °C 25,000 h, Legne control index CRI 80-89, Luminous flux 5000 lm, Rated luminous flux according to IEC 62722-2-1 5000 lm, Lamp light output 100 lm/W, Power factor 0.9, Width 240 mm, Height/depth 60 mm, Length 252 mm, Type of wiring graduation, Number of poles 3, Conductor cross-section 0.75 mm², Connectable conductor cross-section 0.75 mm², Connectable conductor cross-section 0.75 mm², Connectable conduc

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

