



Soft starter Sirius 45kW/400V, 24V - Soft starter 80A 24VAC 24VDC 3RW4046-2BB04



Siemens
3RW4046-2BB04
 4011209696488 EAN/GTIN

973,85 GBP excl. VAT**
 plus shipping



14-16 days* (GBR)

Sirius soft starter 45kW/400V, 24V 3RW4046-2BB04 Rated operational current Ie at 40 °C Tu 80A, rated operational voltage Ue 200 ... 480V, rated power three-phase motor, standard circuit, at 230 V 22kW, rated power three-phase motor, standard circuit, at 400 V 45kW, function one direction of rotation, Rated ambient temperature without derating 40°C, Rated control supply voltage Us at AC 50 Hz 24 ... 24V, Rated control supply voltage Us at AC 60 Hz 24 ... 24V, Rated control supply voltage Us at DC 24 ... 24V, Type of voltage for actuation AC/DC, integrated Motor overload protection, degree of protection (IP) IP00, SIRIUS S3 soft starter 80 A, 45 kW/400 V, 40 °C 200-480 V AC, 24 V AC/DC Spring-loaded terminals SIRIUS 3RW40 soft starter for standard applications for smooth starting and stopping of three-phase asynchronous motors. Infinitely variable starting, reduction of current peaks, avoidance of mains voltage fluctuations during start-up, relief of the power supply network, reduction of the mechanical load in the drive, significant space and wiring savings compared to star-delta starters and frequency converters, maintenance-free switching and extremely easy handling. The integrated bypass enables the very compact design and ensures less heating in the control cabinet. Intelligent monitoring functions protect the soft starter from overheating and the motor from overload. In addition, you can limit the current during startup to an adjustable maximum value. With the integrated remote reset, you can quickly and easily fix faults remotely. Worldwide approvals (eg IEC and UL/CSA) also for potentially explosive applications (ATEX or IEC Ex). The 3RW soft starters are available for supply systems up to 690 V in a large power range with different control supply voltages and consistently with screw and spring-type terminals. For 3RW30/40 there are additional versions with 24 V control supply voltage. Some of the 3RW40 up to size S3 and all 3RW44 also offer thermistor motor protection. With the optional link module, the soft starters can be attached to the circuit breakers, even for the versions with spring-type terminals. The optional fan enables an even tighter design in the control cabinet. Simple, efficient, always up-to-date - the SIRIUS modular system.

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

