



## Wall motion detector 180 degrees - Movement sensor 180° 3m MD180i/16BASICSetEXX



**ESYLUX**  
MD180i/16BASICSetEXX  
EB10430633  
4015120430633 EAN/GTIN

**59,42 GBP** excl. VAT\*\*  
plus shipping

 14-16 days\* (GBR)

Wall motion detector 180 degrees MD180i/16BASICSetEXX Version motion detector, sensor type passive infrared, animal path, scan angle 180°, optimal mounting height 1.1m, stairwell monitoring, max. range to one side 8m, max. frontal range 6m, detection field diameter on the floor 16m, remote controllable, Response brightness adjustable, suitable for wall mounting, flush-mounted installation type, screw terminal connection type, plastic material, thermoplastic material quality, halogen-free, surface untreated, surface design matt, color white, RAL number (similar) 9010, protection class (IP) IP40, type of voltage AC, frequency 50 ... 50Hz, nominal voltage 230V, min. duty cycle 60s, max. duty cycle 60min, switch-off delay 3600s, switch-on delay 0s, horizontal detection angle 180 ... 180°, sensor swivel range, horizontal 0°, sensor swivel range, vertical 0°, response brightness 5 ... 2000lx, max. switching capacity 2300W, suitable for C-load, temperature 0 ... 50°C, number of switching zones n 1, max. inrush current 800A, control current 0mA, extension input, width 70mm, height 55mm, depth 70mm, installation width 45mm, installation depth 24mm, installation length 45mm, installation diameter 60mm, min. depth of the device box 24mm, wall motion detector with 180° detection range. 16 A high-performance relay (tungsten pre-contact). Especially suitable for switching capacitive loads such as e.g. E.g. electronic ballasts, parallel-compensated fluorescent lamps, compact fluorescent lamps, energy-saving lamps. Programmable by remote control, e.g. B. Permanent light ON/OFF and automatic read-in function of the current light value. Cover frames in 5 different colors and brand switches compatible, thus replacing any conventional switch. Design in IP 40 suitable for damp rooms, garages, basement exits. Anti-vandal cover with stainless steel screws (accessories). Prevention of unwanted switching, e.g. B. by small animals, by hiding the vertical detection area using the enclosed cover cap. Universal surface-mounted box IP 20/IP 44 with triple membrane cable entry. Integrated pulse function for controlling automatic staircase lighting or signaling devices and use for building technology/PLC.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

