

Item Number EB10652364

×

https://www.eibabo.uk/abb/circuit-breaker-10ka-15a-4p-miniature-circuit-breaker-4-p-k15a-su204m-k15 -eb10652364

Circuit breaker 10kA 15A 4P - Miniature circuit breaker 4p K15A SU204M-K15

ABB SU204M-K15 2CDS274337R0457 4016779930635 EAN/GTIN

211,95 GBP excl. VAT**

plus shipping



Automatic circuit breaker 10kA 15A 4P SU204M-K15 tripping characteristic K, number of poles (total) 4, number of fused poles 4, rated current 15A, rated voltage 480V, rated insulation voltage Ui 440V, rated switching capacity Icn according to EN 60898 at 400 V 11.2kA, rated switching capacity Icu according to IEC 60947- 2 at 230 V 15kA, rated switching capacity Icu according to IEC 60947- 2 at 400 V 15kA, type of voltage AC/DC, frequency 0 ... 60Hz, energy limitation class 3, overvoltage category 3, degree of pollution 3, additional equipment possible, width in modular units 4, installation depth 69mm, Degree of protection (IP) IP20 Ambient temperature during operation -25 ... 55°C Connectable conductor cross-section stranded 0 ... 25mm² Connectable conductor cross-section solid 0 ... 35mm² The circuit breakers of the SU 200 M series protect cables and lines from overload and short circuit according to DIN VDE 0100-430 and DIN VDE 0100-530. They meet the building regulations DIN VDE 0660-101 or IEC/EN60947-2 and UL489 or CSA 22.2 No. 5. Its patented connection terminal ensures simple and safe contacting and handling using a pressure plate. For better visibility when wiring, the connection opening for cables is above the connection opening for the busbar. Conductor cross-sections up to 35 mm² can be connected directly to the device via the connection terminal with insulation in protection class IP20. The extensive range of accessories offers you everything you need for your installation tasks. The combination of approvals according to UL489, CSA 22.2 no. 5 and IEC/EN60947-2 make this device a device that can be used worldwide for high demands and is subjected to three intensive tests for quality and performance before delivery.

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

