

## Item Number EB17710112

https://www.eibabo.uk/schneider-electric/safety-relay-10fct-1circle-1nc-2t-safety-relay-24v-ac-dc-en954 -1-cat-4-xpsuat13a3ac-eb17710112



## Safety relay 10Fct 1circle 1NC 2T - Safety relay 24V AC/DC EN954-1 Cat 4 XPSUAT13A3AC

×

Schneider Electric

XPSUAT13A3AC 3606489601683 EAN/GTIN

189,89 GBP excl. VAT\*\*

plus **shipping** 



14-16 days\* (GBR)

Safety relay 10Fkt 1Kreis 1Ö 2T XPSUAT13A3AC Basic device version, Suitable for monitoring position switches, Suitable for monitoring EMERGENCY STOP circuits, Suitable for monitoring optoelectronic protective devices, Suitable for monitoring magnetic switches, Suitable for monitoring proximity switches, Design of the electrical connection Spring-loaded connection, DIN rail mounting possible, Rated control supply voltage Us at AC 50 Hz 24 ... 24V, Rated control supply voltage Us at AC 60 Hz 24 ... 24V, Rated control supply voltage Us at DC 24 ... 24V, Type of voltage for actuation AC/DC, With removable terminals, Evaluation of Two-channel inputs, with start input, with feedback circuit, off-delay 0 ... 900s, number of outputs, safety-related, undelayed, with contacts 3, number of outputs, safety-related, delayed, with contacts 4, number of outputs, safety-related, undelayed, semiconductor 0, number of exits, itself safety-related, delayed, semiconductor 0, number of outputs, signaling function, instantaneous, contact-based 0, number of outputs, signaling function, delayed, contact-based 0, number of outputs, signaling function, instantaneous, semiconductor 0, number of outputs, signaling function, delayed, semiconductor 0, category according to EN 954-14, safety type according to IEC 61496-14, stop category according to IEC 602040+1, performance level according to EN ISO 13849-1 level e, SIL according to IEC 61508 3, with TÜV approval, with approval according to UL, width 45mm, height 100mm, depth 120mm, safety relay Preventa XPS Universal. Multifunctional safety relay for a wide range of safety applications thanks to the selectable safety function and start option using the rotary switch on the front, as well as diagnostic communication with the PLC. Suitable for mechanical contacts in emergency off/stop, position or magnetic switches, safety mats and electronic PNP/NPN sensors, light curtains or RFID safety switches with OSSD outputs. Selectable start function automatic, manual or monitored start, as well as start-up test. Number of safety circuits 1 (redundant) - Selectable safety function 1 from 10. Safe relay outputs 3S undelayed+3S optionally delayed+1NC - Status 1T Diagnosis 1T. Safe switch-off delay 0.1 second to 15 minutes for SS1 or Stop1 function. Pulsed output transmits extensive diagnostic data to the PLC at the standard input and evaluation via FB. Safety level PL e, cat. 4, SIL3. Supply voltage 24 VAC/DC. Connections removable spring terminals. Lateral connector for direct connection of contact expansion without wiring.

## YOUR ADVANTAGES



**WORLDWIDE TRADE** Corporate video eibmarkt®



**COMPLAINTS HANDLING** Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



**DHL TRACK & TRACE** Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL). \*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

