



**LED pendant lamp 4000K - Pendant luminaire 1x46W  
stail-S #60334024195**



**Regiolux**  
stail-S #60334024195  
60334024195  
4020863322503 EAN/GTIN

**252,37 GBP** excl. VAT\*\*  
plus shipping bulky item



3-5 days\* (GBR)

Suitable for computer workstations according to EN 12464-1 yes, Suitable for light band configuration yes, Suitable for number of lamps 1, Version without, Material of the housing Steel, Housing Color gray, Material of the cover Textured plastic, Execution of the grid without, Voltage AC, Nominal voltage 230V, Current 200 mA, Control gear LED operating device current-controlled, With operating device yes, Replaceable operating device no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DALI-2 no, Dimming DMX no, Programmable dimming no, Dimming DSI no, Dimming RF no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, light distributor Diffuser lens / optics / panel, Reflector without, Light distribution symmetrical, Colour consistency (McAdam ellipse) SDCM3, Light output direct / indirect, Direct / indirect shares separately adjustable no, Rated service life L80/B10 at 25 °C 50000 h, IP protection) IP20, Protection class (NEMA) other, Impact resistance IK03, Protection class I, Suitable for emergency light no, Integrated emergency power supply no, Glow wire test according to IEC 60695-2-11 without, Suitable for lamp power 46 W, Max. System performance 46 W, Rated luminous flux according to IEC 62722-2-1 6700 lm, Light color white, luminous efficacy 144 lm/W, Color temperature 4000K, Color rendering index CRI 80-89, Glare reduction (UGR) 14.2, Colour temperature adjustable no, Light current adjustable infinitely variable, Beam angle adjustable no, Width 198 mm, Height / depth 37 mm, Length 1540 mm, With suspension no, Pendulum length 150..1900 mm, Number of poles 3, Connection Plug-in terminal, Compatible with Apple HomeKit no, Compatible with Google Assistant no, Compatible with Amazon Alexa no, IFTTT support available no, Lamp LED not interchangeable, With bulbs yes

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

**eibabo®** and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

**eibabo®** the Smart Home technology shop  
**eibabo®** electronics cheap online order  
**eibabo®** electric appliances buy online

