

https://www.eibabo.uk/rademacher/belt-winder-rollotron-comfort-duofern-plus-belt-winding-motor-built-in-1805-uw-eb17001805



Belt winder RolloTron Comfort DuoFern Plus - Belt winding motor built-in 1805-UW

×

Rademacher

1805-UW 16236011 4031909018809 EAN/GTIN

200,14 GBP excl. VAT**

plus shipping



14-16 days* (GBR)

Belt winder RolloTron Comfort DuoFern Plus 1805-UW, mounting type=installation, belt thickness=23 mm, belt length=10200 mm, max. roller shutter weight=60 kg, with timer=yes, height=180 mm, width=61 mm, depth=197 mm, With sun sensor=no, the Comfort Funk Plus belt winder is an electronic belt winder for flush-mounted installation that was specially developed for large belt boxes. It is characterized by quick and easy assembly. Installation and commissioning takes about 10 minutes. It is operated via a Euro plug connection to the 230V power network. It is the successor to the Comfort Funk Plus model from RADEMACHER's 9800 series. The new Comfort Funk Plus belt winder appears in a modern design with a large, illuminated display with contrast adjustment and is delivered in the color ultra white. It has an installation wizard and an integrated interface for easy and quick integration into the radio system. It can be controlled remotely using a radio transmitter. Used as a central control, it can send automatic commands to the registered radio receivers. It has extensive automatic functions such as the daily, weekly, weekend and astro program as well as the random function. The ventilation and sun position can be freely selected. A simple approach to intermediate positions is also possible. The summer/winter time changeover occurs automatically and a key lock can be set to prevent unwanted operation. The model has permanent data storage in the event of a power failure. The soft start/soft stop function enables quiet running with a high level of comfort. In standby, the Comfort Funk Plus belt winder consumes less than 0.6 W. A belt with a width of 23 mm must be used with this model. If the webbing thickness is 1.0 mm, a winding capacity of 15 m is achieved and with a thickness of 1.3 mm, 12 m. To ensure smooth operation, the permissible roller shutter area of approx. 10 m² with a roller shutter weight of 4 kg/m² or approx. 6 m² with 7 kg/m² must be adhered to. Sun/twilight control is possible with the S/D sensor, which

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

