



Insulation timer Igr - Twilight switch 2...300lx 544890



Merten
544890
4011281851508 EAN/GTIN

61,39 GBP excl. VAT**
plus shipping

 3-5 days* (GBR)

Insulated timer Igr 544890 Sensor version Built-in light sensor, contacts 1 NO contact, switch-on brightness 2... 300lx, switch-off brightness 2... 300lx, switch-off delay 60s, switch-on delay 60s, max. switching capacity 2300W, suitable for C-load, with automatic night switch-off, Type of mounting surface-mounted, material plastic, material quality thermoplastic, halogen-free, surface untreated, surface finish glossy, color grey, RAL number (similar) 7035, nominal voltage 230V, max. switching current (resistive load) 10A, suitable for protection class (IP) IP54, Water-protected surface-mounted device with impact-resistant housing. With time function. The twilight timer combines the functions of a twilight switch and a timer in one device. You can choose between three functions: Twilight function: When the twilight threshold is reached, the lighting is switched on in the evening and switched off in the morningxx Automatic function: In the evening, the lighting is switched on when the set twilight threshold is reached and again at a preset time (e.g. 11 p.m.), switched off. In the morning, the lighting is switched on again at a preset time (e.g. 5:00 a.m.) and switched off after the twilight threshold has been reached. Semi-automatic function: In the evening, the lighting is switched on when the set twilight threshold is reached and switched off again at a preset time (e.g. 11:00 p.m.). An integrated special function ensures that the time is automatically adjusted to the ambient brightness. Manual setting of the time is not required. Relay with u contact. High sensitivity to light. Automatic time adjustment. Large connection room. Connected load: up to 2300 VA. Max. switching current: AC 230 V, 10 A cos phi 0.6. Halogen lamps: AC 230 V, up to 2000 W. Incandescent lamps: AC 230 V, up to 2300 W. Capacitive load: max. 140 uF. Connection terminals: for 2.5 mm² solid conductors. Setting range/switching threshold: 2 to 300 lux, adjustable. Degree of protection: IP 54. Dimensions: approx. 97x80x47 mm. Accessories: Capacitor 542895. Colour: light grey.

YOUR ADVANTAGES

 **WORLDWIDE TRADE**
Corporate video eibmarkt®

 **99% CUSTOMER SATISFACTION**
> 500,000 customers worldwide

 **DHL TRACK & TRACE**
Shipment tracking

 **COMPLAINTS HANDLING**
Obliging and 100% safely

 **25 YEARS OF EXPERIENCE**
In worldwide mail order

 **ORDER LIVE CHAT**
With order history

 **SHORT DELIVERY TIME**
Warehousing

 **REFUND**
Within 14 days

 **DATA PROTECTION**
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

