

## Item Number EB10728477

https://www.eibabo.uk/siemens/terminal-module-tm-e15c24-01-fieldbus-mounting-frame-2-slot-6es719 34cb300aa0-ve5-eb10728477



## Terminal module TM-E15C24-01 - Fieldbus mounting frame 2 slot 6ES71934CB300AA0 (VE5)

×

## Siemens

6ES71934CB300AA0 (VE5) 6ES71934CB300AA0 4025515059912 EAN/GTIN

**77,93 GBP** excl. VAT\*\*

plus shipping



3-5 days\* (GBR)

Terminal module TM-E15C24-01 6ES71934CB300AA0 VE5 input voltage at AC 50 Hz 24... 230V, input voltage at AC 60 Hz 24... 230V, input voltage at AC 50 Hz 10A, Max. input current at AC 50 Hz 10A, Max. input current at DC 10A, Output voltage at AC 50 Hz 24... 230V, Output voltage at AC 60 Hz 10A, Max. output current at AC 50 Hz 10A, Max. output current at AC 50 Hz 10A, Max. output current at AC 50 Hz 10A, Max. output current at AC 60 Hz 10A, Max. output current at DC 10A, System component, Number of slots 2, With plug-in modules, digital I/O, With pluggable assemblies, analog I/O, with pluggable assemblies, communication modules, with pluggable assemblies, function and technology modules, with pluggable assemblies, other, mounting possible, explosion protection category for gas ATEX gas explosion protection, cat. 3G, explosion protection category rie for dust without, width 15mm, height 132mm, depth 43mm, terminal modules are purely mechanical components for building the ET 200S. They accommodate the electronic and power modules. The modules are automatically coded the first time they are plugged in. Self-assembling potential rails integrated in the terminal modules significantly reduce the wiring effort and the required control cabinet space. The self-constructing shielding of the backplane bus increases data security. Robust design and form-fitting connection technology enable use in harsh industrial environments (e.g. vibration resistance up to 5 g). There are different versions of terminal modules: "Terminal modules for power modules (TM-P): For feeding in load/encoder voltage on two self-assembling potential rails. A third potential rail (AUX1, max. 230 V) can be individually connected, e.g. B. can be used for the permanent supply of light barriers or PE. Power modules for voltage monitoring and protection are plugged onto TM-P modules. TM-P modules can be used any number of times at any point w

## YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

