



LED moisture-proof luminaire 4000K DALI - Ceiling-/wall luminaire AragF 15 P #7403151



Trilux
AragF 15 P #7403151
7403151
4018242516551 EAN/GTIN

312,29 GBP excl. VAT**
plus shipping bulky item

 14-16 days* (GBR)

Suitable for wall mounting yes, Suitable for pendulum suspension yes, Suitable for ceiling mounting yes, Suitable for recessed mounting no, Suitable for surface mounting yes, Suitable for light band configuration no, Suitable for number of lamps 1, Version other, Material of the housing Plastic, Housing Color gray, Material of the cover Plastic transparent, Execution of the grid without, Voltage AC, Nominal voltage 220..240 V, Control gear electronic transformer, With operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI-2 yes, Dimming DALI yes, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming yes, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim yes, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function no, light distributor focus lens, Light distribution symmetrical, Beam angle wide beam 41-80, Colour consistency (McAdam ellipse) SDCM3, Light output direct / indirect, IP protection) IP66, Protection class (NEMA) other, Impact resistance IK03, Protection class I, Suitable for emergency light no, Integrated emergency power supply no, With motion detector yes, With light sensor yes, With louvers no, Max. System performance 43 W, luminous efficacy 146 lm/W, Rated luminous flux according to IEC 62722-2-1 6300 lm, Light color white, Color temperature 4000K, Flicker value Pst LM 18457 lm, Color rendering index CRI 80-89, Power factor 280000 h, Stroboscopic effect value SVM 18457 lm, Width 102 mm, Height / depth 91 mm, Length 1552 mm, Type of wiring with through-wiring, Number of poles 5, Cross section 1.5 mm², Connection Plug-in terminal, Distortion factor (THD) 14, Photobiological safety according to EN 62471 RG0, Colour temperature adjustable no, Light current adjustable no, Beam angle adjustable no, Lamp LED not interchangeable, With bulbs yes

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

