



**LED recessed light 3000K, DALI - Ceiling-/wall luminaire
ArimoFit M48#7531251**



Trilux
ArimoFit M48#7531251
7531251
4018242522989 EAN/GTIN

337,83 GBP excl. VAT**
plus shipping bulky item

 **14-16 days* (GBR)**

Suitable for wall mounting no, Suitable for pendulum suspension no, Suitable for ceiling mounting no, Suitable for recessed mounting yes, Suitable for surface mounting no, Suitable for light band configuration no, Suitable for computer workstations according to EN 12464-1 yes, Suitable for number of lamps 1, Version other, Material of the housing Aluminum, Surface protection Housing powder-coated, Housing Color white, Material of the cover Textured plastic, Execution of the grid without, Voltage DC, Nominal voltage 220..240 V, Control gear LED operating device current-controlled, With operating device yes, Replaceable operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI-2 yes, Dimming DALI yes, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim yes, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function no, light distributor other, Light distribution symmetrical, Beam angle medium-emitting 21-40°, Colour consistency (McAdam ellipse) SDCM3, Light output directly, Rated service life L70/B50 at 25 °C 100000 h, Rated service life L80/B10 at 25 °C 50000 h, Rated service life L90/B10 at 25 °C 50000 h, IP protection) IP20, Protection class (NEMA) other, Impact resistance IK02, Protection class II, Suitable for emergency light no, Integrated emergency power supply no, With motion detector no, With light sensor no, With louvers no, Max. System performance 42 W, luminous efficacy 119 lm/W, Rated luminous flux according to IEC 62722-2-1 5000 lm, Light color white, Color temperature 3000K, Flicker value Pst LM 18457 lm, Color rendering index CRI 80-89, Power factor 280000 h, Stroboscopic effect value SVM 18457 lm, Width 296 mm, Height / depth 22 mm, Length 1496 mm, Installation length 1496 mm, Installation width 296 mm, Installation height / depth 160 mm, Type of wiring graduation, Number of poles 5, Connection Plug-in terminal, Distortion factor (THD) 14, Photobiological safety according to EN 62471 RG0, Glare reduction (UGR) 19, Colour temperature adjustable no, Light current adjustable no, Beam angle adjustable no, Lamp LED not interchangeable, With bulbs yes

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

