

LED recessed light 840, DALI - Ceiling-/wall luminaire Creavo M59 #7624251



Trilux
 Creavo M59 #7624251
 7624251
 4018242568260 EAN/GTIN

391,42 GBP excl. VAT**
 plus shipping bulky item

 14-16 days* (GBR)

Suitable for wall mounting no, Suitable for pendulum suspension no, Suitable for ceiling mounting yes, Suitable for recessed mounting yes, Suitable for surface mounting no, Suitable for light band configuration no, Suitable for computer workstations according to EN 12464-1 yes, Suitable for number of lamps 1, Version other, Material of the housing Steel, Housing Color white, Material of the cover other, Execution of the grid without, Voltage DC, Nominal voltage 220..240 V, Control gear electronic transformer, With operating device yes, Replaceable operating device yes, Dimming 0-10 V no, Dimming 1-10 V yes, Dimming DALI-2 yes, Dimming DALI yes, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim yes, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function no, light distributor focus lens, Light distribution symmetrical, Beam angle wide beam 41-80, Colour consistency (McAdam ellipse) SDCM3, Light output directly, IP protection) IP20, Protection class (NEMA) other, Impact resistance IK02, Protection class I, Suitable for emergency light no, Integrated emergency power supply no, With motion detector no, With light sensor no, With louvres no, Max. System performance 32 W, luminous efficacy 45,4 W, Rated luminous flux according to IEC 62722-2-1 5300 lm, Light color white, Color temperature 4000K, Flicker value Pst LM 18457 lm, Color rendering index CRI 80-89, Power factor 280000 h, Stroboscopic effect value SVM 18457 lm, Width 310 mm, Height / depth 50 mm, Length 1547 mm, Installation length 1524 mm, Installation width 287 mm, Installation height / depth 180 mm, Type of wiring graduation, Number of poles 5, Connection Plug-in terminal, Distortion factor (THD) 14, Photobiological safety according to EN 62471 RG1, Glare reduction (UGR) 19, Colour temperature adjustable no, Light current adjustable no, Beam angle adjustable no, Lamp LED not interchangeable, With bulbs yes

YOUR ADVANTAGES



WORLDWIDE TRADE
 Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
 > 500,000 customers worldwide



DHL TRACK & TRACE
 Shipment tracking



COMPLAINTS HANDLING
 Obliging and 100% safely



25 YEARS OF EXPERIENCE
 In worldwide mail order



ORDER LIVE CHAT
 With order history



SHORT DELIVERY TIME
 Warehousing



REFUND
 Within 14 days



DATA PROTECTION
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
 eibabo® electronics cheap online order
 eibabo® electric appliances buy online

