



**LED downlight 4000K - Downlight/spot/floodlight 1x12W
loda-LDESO1400840ET**



Regiolux
loda-LDESO1400840ET
37670204140
4020863333820 EAN/GTIN

50,15 GBP excl. VAT**
plus shipping

 **14-16 days*** (GBR)

Suitable for wall mounting no, Suitable for recessed mounting yes, Suitable for surface mounting no, Suitable for pendulum suspension no, Suitable for ceiling mounting yes, Suitable for truss mounting no, Suitable for pedestal / floor mounting no, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability not adjustable, With motion detector no, With light sensor no, Lamp LED not interchangeable, With bulbs yes, Suitable for number of lamps 1, Version other, Material of the housing Aluminum, Surface protection lacquered, Housing Color white, Material of the cover Plastic opal, Surface brushed no, Voltage AC, Nominal voltage 230V, Control gear LED operating device current-controlled, With operating device yes, Replaceable operating device no, Dimming dependent on control gear yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI-2 no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, Reflector without, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle wide beam 41-80, Light output directly, Rated service life L80/B10 at 25 °C 50000 h, IP protection) IP44, Protection class (NEMA) other, Impact resistance IK00, Protection class II, Suitable for lamp power 12 W, Max. System performance 12 W, Light color white, Color temperature 4000K, Color rendering index CRI 80-89, Luminous flux 1400 lm, Rated luminous flux according to IEC 62722-2-1 1400 lm, Colour temperature adjustable no, Light current adjustable infinitely variable, Beam angle adjustable no, Height / depth 74 mm, Outer diameter 204 mm, Installation height / depth 105 mm, Installation diameter 190 mm, Type of wiring graduation, Number of poles 2, Connection other, Integrated emergency power supply no, Glow wire test according to IEC 60695-2-11 without, luminous efficacy 124 lm/W, Photobiological safety according to EN 62471 other, IFTTT support available no, Colour consistency (McAdam ellipse) SDCM3, Glare reduction (UGR) 26.1, Compatible with Apple HomeKit no, Compatible with Google Assistant no, Compatible with Amazon Alexa no

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

