

**LED recessed downlight 840, BMW, white -
Downlight/spot/floodlight 1x14,1W 901453.002.1.19**



RZB

901453.002.1.19

4051859685760 EAN/GTIN



119,70 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

Suitable for wall mounting no, Suitable for recessed mounting yes, Suitable for surface mounting no, Suitable for pendulum suspension no, Suitable for ceiling mounting yes, Suitable for truss mounting no, Suitable for pedestal / floor mounting no, Suitable for track mounting no, Suitable for clamp mounting no, Suitable for rope system no, Adjustability not adjustable, With motion detector yes, With light sensor no, Lamp LED not interchangeable, With bulbs yes, Suitable for number of lamps 1, Version without, Material of the housing Aluminum, Surface protection other, Housing Color white, Surface brushed no, Voltage AC, Nominal voltage 220..240 V, Control gear LED operating device current-controlled, With operating device yes, Dimming dependent on control gear no, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Without dimming function yes, Reflector without, light distributor without, Light distribution symmetrical, Beam angle free radiate/diffuse, Light output directly, Distortion factor (THD) 0.2, IP protection) IP54, Impact resistance IK04, Protection class I, Suitable for lamp power 14,1 W, Max. System performance 17 W, Light color white, Color temperature 4000K, Color rendering index CRI 80-89, Luminous flux 1800 lm, Rated luminous flux according to IEC 62722-2-1 1800 lm, Power factor 26383 lm, Height / depth 3 mm, Outer diameter 255 mm, Installation height / depth 55 mm, Type of wiring graduation, Number of poles 3, Cross section 1.5 mm², Connectable conductor cross-section 1.5 mm², Connection Plug-in terminal, luminous efficacy 106 lm/W, Photobiological safety according to EN 62471 RG0, Colour consistency (McAdam ellipse) SDCM4

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

