

**LED panel M625 DALI 3000K - Ceiling-/wall luminaire**  
**LEDPane#542004069300**



**Opple Lighting**  
LEDPane#542004069300  
542004069300  
6941497735799 EAN/GTIN

**95,27 GBP** excl. VAT\*\*  
plus shipping bulky item



14-16 days\* (GBR)

Energy efficiency classes spectrum A to G, Suitable for wall mounting no, Suitable for pendulum suspension yes, Suitable for ceiling mounting yes, Suitable for recessed mounting yes, Suitable for surface mounting yes, Suitable for light band configuration no, Suitable for computer workstations according to EN 12464-1 yes, Material of the housing Aluminum, Housing Color white, Material of the cover Textured plastic, Execution of the grid without, Voltage AC/DC, Nominal voltage 220..240 V, Current 750mA, Control gear LED operating device current-controlled, With operating device yes, Replaceable operating device yes, Dimming 0-10 V no, Dimming 1-10 V no, Dimming DALI-2 yes, Dimming DALI yes, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function no, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Colour consistency (McAdam ellipse) SDCM6, Light output directly, Rated service life L70/B50 at 25 °C 70000 h, IP protection) IP54, Impact resistance IK04, Protection class II, Suitable for emergency light no, Integrated emergency power supply no, With motion detector no, With light sensor no, With louvers no, Max. System performance 30 W, luminous efficacy 125 lm/W, Rated luminous flux according to IEC 62722-2-1 3750 lm, Light color white, Color temperature 3000K, Color rendering index CRI 80-89, Power factor 0.9, Constant luminous flux control no, Width 620 mm, Height / depth 9 mm, Length 620 mm, Installation length 620 mm, Installation width 620 mm, Type of wiring graduation, Connection free cable end, Photobiological safety according to EN 62471 RG0, Glare reduction (UGR) 19, Colour temperature adjustable no, Light current adjustable Stages, Beam angle adjustable no, Operation via Bluetooth no, Compatible with Apple HomeKit no, Compatible with Google Assistant no, IFTTT support available yes, Lamp LED not interchangeable, With bulbs yes

**YOUR ADVANTAGES**



**WORLDWIDE TRADE**  
Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
> 500,000 customers worldwide



**DHL TRACK & TRACE**  
Shipment tracking



**COMPLAINTS HANDLING**  
Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
In worldwide mail order



**ORDER LIVE CHAT**  
With order history



**SHORT DELIVERY TIME**  
Warehousing



**REFUND**  
Within 14 days



**DATA PROTECTION**  
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

