



**LED panel Flat Q1 nw dim 1-10V - Ceiling-/wall luminaire
1x18W 1560141143**



Nobile

1560141143

4044538049205 EAN/GTIN

86,27 GBP excl. VAT**

plus shipping



14-16 days* (GBR)

Energy efficiency classes spectrum A to G, Suitable for wall mounting no, Suitable for pendulum suspension yes, Suitable for ceiling mounting no, Suitable for recessed mounting yes, Suitable for surface mounting no, Suitable for light band configuration no, Suitable for number of lamps 1, Version other, Material of the housing other, Housing Color other, Material of the cover other, Execution of the grid other, Voltage AC, Nominal voltage 14070 lm, Control gear electronic transformer, With operating device yes, Dimming 0-10 V no, Dimming 1-10 V yes, Dimming DALI no, Dimming DMX no, Dimming DSI no, Dimming potentiometer (integrated in device) no, GPRS dimming no, Dimming LineSwitch no, Dimming manufacturer-specific no, Dimming Mains voltage modulation no, Dimming Phase section no, Dimming Phase control no, Programmable dimming no, Dimming RF no, Dimming Sine Wave Reduction no, Dimming Touch and Dim no, Dimming Zigbee no, Dimming with push-button no, Dimming dependent on control gear no, Without dimming function no, light distributor Diffuser lens / optics / panel, Light distribution symmetrical, Beam angle extremely wide beam > 80 °, Light output directly, Rated service life L80/B10 at 25 °C 50000 h, IP protection) IP40, Protection class (NEMA) other, Impact resistance IK07, Protection class III, Suitable for emergency light no, With motion detector no, With light sensor no, With louvres no, Suitable for lamp power 18 W, Max. System performance 18 W, luminous efficacy 89 lm/W, Rated luminous flux according to IEC 62722-2-1 1600 lm, Light color other, Color temperature 4000K, Color rendering index CRI 80-89, Power factor 280000 h, Width 310 mm, Height / depth 10 mm, Length 310 mm, Installation length 290 mm, Installation width 290 mm, Connection other, Lamp LED not interchangeable, With bulbs yes

YOUR ADVANTAGES



WORLDWIDE TRADE

Corporate video eibmarkt®



99% CUSTOMER SATISFACTION

> 500,000 customers worldwide



DHL TRACK & TRACE

Shipment tracking



COMPLAINTS HANDLING

Obliging and 100% safely



25 YEARS OF EXPERIENCE

In worldwide mail order



ORDER LIVE CHAT

With order history



SHORT DELIVERY TIME

Warehousing



REFUND

Within 14 days



DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and **eibmarkt®** are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

