



## Axial wall fan AC, explosion protection, DN200 - Ex-proof ventilator EZQ 20/4E E Ex e


**Maico**

EZQ 20/4E E Ex e

0083.0850

4012799838500 EAN/GTIN

**670,20 GBP** excl. VAT\*\*  
plus shipping



14-16 days\* (GBR)

Axial wall fan AC, explosion protection, DN200 EZQ 20/4E E Ex e nominal voltage 230... 230V, frequency 50... 50Hz, power consumption 45kW, housing material steel, unloaded air volume 440m³/h, protection class (IP) IP64, duct width 345mm, channel height 345mm, installation location wall, for Ex zone gas 1, 2, for Ex zone dust without, device group according to Directive 94/9/EC II, explosion protection category for gas ATEX gas explosion protection, cat. 2G, Temperature class according to Directive 94/9/EC T1 to T3, protective grille on the suction side, yellow chromated, contact protection according to DIN EN ISO 13857. 8-bladed impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Installation possible in any position. Conveying direction: The following figure shows the conveying direction: Conveying direction A: Suction via the motor, standard. Conveying direction B: Blowing via the motor, on request. Direction of rotation, reversing operation: The volume flow decreases by approx. 35% if the conveying direction is abnormal. Motor: asynchronous motor. Speed controllable. Exception: Type EZQ 45/6 B, EZS 45/6 B, DZQ 40/2 B and DZS 40/2 B. Reversible. Exception: Fans with shaded-pole motors (...-E). Not suitable for pumping air saturated with water vapor. Three-phase motor: DZQ and DZS series. Rated voltage 400 V, 50 Hz. Protection class IP 55. Exception DZQ/DZS... D IP 54. Thermal overload protection as standard. Exception: Available on request for DZQ/DZS 25/4 D and pole-changing axial wall fans. The connections are potential-free on terminals and must be connected to a full motor protection switch, e.g. MV 25, or the control circuit of a contactor. Pole-changing fans: Ensure overload protection with a full motor protection switch to be provided on site. Pole-changing motors with speed ratios of 8/4 or 4/2 are connected using the Dahlander principle. Electrical connection: To the terminal strip in the end cover of the motor. Safety instructions: The fan may only be put into operation if contact protection of the impeller is guaranteed in accordance with DIN EN ISO 13857. Article: DZQ 25/4 D, design: square wall plate, delivery volume: 1000 m³/h, speed: 1425 1/min, Impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: three-phase current, rated voltage: 400 V, mains frequency: 50 Hz, nominal power: 45 W, Inom: 0.13 A, IMax: 0.13 A, protection class: IP 54, Heat class: B, power supply cable: 5 / 1.5 mm² location: wall / ceiling, installation type: surface-mounted, installation position:...

### YOUR ADVANTAGES


**WORLDWIDE TRADE**

Corporate video eibmarkt®


**COMPLAINTS HANDLING**

Obliging and 100% safely


**SHORT DELIVERY TIME**

Warehousing


**99% CUSTOMER SATISFACTION**

&gt; 500,000 customers worldwide


**25 YEARS OF EXPERIENCE**

In worldwide mail order


**REFUND**

Within 14 days


**DHL TRACK & TRACE**

Shipment tracking


**ORDER LIVE CHAT**

With order history


**DATA PROTECTION**

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler at a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
eibabo® electronics cheap online order  
eibabo® electric appliances buy online

