×



Item Number EB16402440

https://www.eibabo.uk/jung/ceiling-presence-detector-integrated-circuit-part-surface-mounting-presence-detector-3600-dwpm...-eb16402440



Ceiling/presence detector integrated circuit part surface mounting - Presence detector 360° DWPM ...

Jung DWPM K 360 WW 4011377146570 EAN/GTIN

113,16 GBP excl. VAT**

plus **shipping**



3-5 days* (GBR)

Ceiling/presence detector integrated service part AP DWPM K 360 WW Presence detector version, sensor type other, forced switch-off, scan angle 360°, optimum installation height 3m, max. range to one side 10m, max. presence area 314m², detection field diameter on the floor 20m, remote controllable , With remote control, Response sensitivity adjustable, Response brightness adjustable, With signal unit, Teach function for response brightness, Suitable for ceiling mounting, Surface mounting type, Other connection type, Plastic material, Halogen-free, Color white, RAL number (similar) 9010, Type of voltage AC, Frequency 50 ... 60Hz, nominal voltage 230V, switch-off delay 120s, horizontal detection angle 360 ... 360°, response brightness 5 ... 1000lx, max. switching capacity 2300W, suitable for C-load, temperature -5 ... 45°C, max. Inrush current 16A, min. inrush current 16A, extension input, alarm function, depth 66mm, diameter 103mm, ceiling monitor/presence detector, with integrated power unit, surface-mounted, AC 1 10 to 230 V ~, mains frequency: 50 / 60 Hz, connected load at AC 230 V ~ and 35 °C: 2300 W incandescent lamps, 2000 W HV halogen lamps, 1500 W Tronic transformers, 1000 VA inductive transformers, HV LED lamps typically 400 W, compact fluorescent lamps typically 400 W, fluorescent lamps 920 VA (uncompensated) and capacitive load 690 VA (560 µF), connected load at AC 110 V ~ and 35 °C: incandescent lamps 1150 W, HV halogen lamps 1000 W, Tronic transformers 750 W, inductive transformers 500 VA, HV LED lamps typically 200 W, compact fluorescent lamps typically 200 W, fluorescent lamps 460 VA (uncompensated) and capacitive load 345 VA (560 µF), switching current at 35 °C: ohmic 16 A (AC1) and Fluorescent lamps: 4 AX, minimum switching current AC: 100 mA, detection angle: 360°, detection range: Ø approx. 20 m, sensitivity: 25 to 100%, brightness setting: approx. 5 to 2000 lx and daytime operation, follow-up time: approx. 10 to 30 seconds minutes, short-term operation: pulse duration: approx. 0.5 seconds and pulse pause approx. 3 seconds, 2-point light control, F Functions can be set with IR remote controls, operation with IR remote control, 2-wire extension or installation button, teach function for adjusting the brightness threshold, in combination with IR remote controls, switch-off early warning, short-term operation, e.g. for activating acoustic signaling devices, LED display, presence simulation, function as a twilight switch, dynamic follow-up time, detection field can be restricted by switching off individual sensors or a clip-on cover, detection area can be expanded by connecting...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries

outside the EU.

**** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

