



## Belt winder RolloTron Comfort DuoFern etc - Belt winding motor built-in 1800-UW



**Rademacher**  
 1800-UW  
 16234511  
 4031909018786 EAN/GTIN

**149,48 GBP** excl. VAT\*\*  
 plus shipping



3-5 days\* (GBR)

Belt winder RolloTron Comfort DuoFern uws 1800-UW installation type, belt thickness 23mm, belt length 6200mm, max. roller shutter weight 45kg, with timer, height 132mm, width 61mm, depth 139mm, The belt winder Comfort Funk is an electronic belt winder for flush-mounted installation and can be used universally because it fits into any standard belt box from 36 mm wide. It is characterized by quick and easy assembly. Installation and commissioning takes about 10 minutes. It is operated via a Euro plug connection to the 230V power network. It is the successor to the Comfort radio model from the 9800 series from RADEMACHER. The new Comfort Funk belt winder appears in a modern design with a large, illuminated display with contrast adjustment and is delivered in ultra white. It has an installation wizard and an integrated interface for easy and quick integration into the radio system. It can be controlled remotely using a radio transmitter. Used as a central control, it can send automatic commands to the registered radio receivers. It has extensive automatic functions such as the daily, weekly, weekend and astro program as well as the random function. The ventilation and sun position can be freely selected. A simple approach to intermediate positions is also possible. The summer/winter time changeover occurs automatically and a key lock can be set to prevent unwanted operation. The model has permanent data storage in the event of a power failure. The soft start/soft stop function enables quiet running with a high level of comfort. In standby, the Comfort Funk belt winder consumes less than 0.6 W. A belt with a width of 23 mm must be used with this model. If the webbing thickness is 1.0 mm, a winding capacity of 7.6 m is achieved and with a thickness of 1.3 mm 6.2 m. To ensure smooth operation, the permissible roller shutter area of approx. 6 m² with a roller shutter weight of 4 kg/m² or approx. 3 m² with 7 kg/m² must be adhered to. Sun/twilight control is possible with the S/D sensor, which is available as an accessory.

### YOUR ADVANTAGES



**WORLDWIDE TRADE**  
 Corporate video eibmarkt®



**99% CUSTOMER SATISFACTION**  
 > 500,000 customers worldwide



**DHL TRACK & TRACE**  
 Shipment tracking



**COMPLAINTS HANDLING**  
 Obliging and 100% safely



**25 YEARS OF EXPERIENCE**  
 In worldwide mail order



**ORDER LIVE CHAT**  
 With order history



**SHORT DELIVERY TIME**  
 Warehousing



**REFUND**  
 Within 14 days



**DATA PROTECTION**  
 Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company ([www.eibmarkt.de](http://www.eibmarkt.de)). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop  
 eibabo® electronics cheap online order  
 eibabo® electric appliances buy online

