https://www.eibabo.uk/jung/brightness-controller-knx-flush-mounted-knx-brightness-sensor-2096-lux-eb16516042

Brightness controller KNX flush-mounted - KNX brightness sensor 2096 LUX

Jung
2096 LUX
4011377127517 EAN/GTIN

77,42 GBP excl. VAT**
plus **shipping**

14-16 days* (GBR)

Brightness controller KNX UP 2096 LUX bus system KNX, other bus systems without, type of installation flush-mounted, version of the sensor built-in light sensor, with bus coupling, number of channels 1, setting 1 ... 2000lx, KNX brightness controller, flush-mounted, with integrated bus coupler, nominal voltage KNX: DC 21 up to 32 V SELV, current consumption KNX: 15 mA, connection KNX: connection and branch terminal, measuring range: 0 to 2000 lx, humidity: maximum 93% relative humidity, no condensation, ambient temperature: - 5 to + 45 °C, storage and Transport temperature: - 25 to + 70 °C, protection class: III, dimensions without cover (W x H x D): 50 x 35 x 15 mm, for measuring and controlling indoor lighting

YOUR ADVANTAGES

WORLDWIDE TRADE
Corporate video eibmarkt®

99% CUSTOMER SATISFACTION
> 500,000 customers worldwide

DHL TRACK & TRACE
Shipment tracking

COMPLAINTS HANDLING
Obliging and 100% safely

25 YEARS OF EXPERIENCE
In worldwide mail order

ORDER LIVE CHAT
With order history

SHORT DELIVERY TIME
Warehousing

REFUND
Within 14 days

DATA PROTECTION
Guarantee

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online