

30 V ----

R

KNX

TP/S In 2 / YE

KNX+ / RD

KNX 7 BK

In 1 / GN

/ WH

Adr.

µ6A 230V ~ AC1

Hager Controls - BP10140 67703 SAVERNE CEDEX

Hager Ltd-Hortonwood 50 TELFORD-TF1 7FT-UK

:hager

TXB692F

Item Number EB16518262

×

https://www.eibabo.uk/hager/knx-switching-actuator-2-fold-or-blind-actuator-1-fold-including-2-binary-in puts-txb692f-eb16518262

KNX switching actuator 2-fold or blind actuator 1-fold, including 2 binary inputs TXB692F Hager TXB692F

3250616048881 EAN/GTIN

66,37 GBP excl. VAT**

plus shipping



Switching/blind output easy 2/1f,2InputUP,6A TXB692F bus system KNX, other bus systems without, type of installation flush-mounted, width in modular units 0, with bus coupling, on-site/manual operation, with LED display, number of inputs 2, switching current ohmic 6A, Max. switching capacity 1380W, Max. number of blind outputs 1, Type of current DC, Degree of protection (IP) IP20, Min. depth of the device box 40mm, Switch/blind actuator 2/1-gang + 2 inputs KNX easy, 6A, UP. Flush-mounted switch/blind actuator with potential-free NO contacts for switching independent loads or for controlling a motor drive as well as additional binary inputs for connecting conventional buttons/switches. With integrated bus coupler, KNX bus connection via pre-assembled cable, load screw terminals. LED button for manual operation or as a programming button. Functions: ON/OFF, timer function with switch-off early warning, priority control with status display, automatic function can be activated/deactivated, load shedding by channel deactivation, 64 scene functions. Roller shutter/blind function: up/down operation with slat angle adjustment, positioning function and slat adjustment for blinds in percent parameterization. Status objects for the position of the slats in percent and the upper/lower end position. Forced control with status display and 3 alarm objects with different priority control. Automatic function can be activated/deactivated, 64 scene functions per channel and adjustable sun protection function. Binary input functions: 2 independent binary inputs, Toggle, switching, time switch, shutter/blinds, dimming, heating, priority control, scene, alarm, automatic deactivation, load shedding, window contact and tariff. Note: The device can be programmed using the easy commissioning tool, easy configuration server or the ETS (from version 4). Observe the instructions of the roller shutter/blind motor manufacturer.

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

