

https://www.eibabo.uk/philips-licht/led-light-carrier-white-g2-491-40s-840-psd-gear-tray-for-light-line-sy stem-4mx850-66744499-eb11576786



## LED light carrier white G2 491 40S/840 PSD - Gear tray for light-line system 4MX850 #66744499

×

Philips Licht 4MX850 #66744499 66744499 4030732667444 EAN/GTIN

**121,67 GBP** excl. VAT\*\*

plus **shipping bulky item** 



14-16 days\* (GBR)

LED light carrier ws G2 491 40S/840 PSD 4MX850 66744499 Illuminant LED not interchangeable, With illuminant, Suitable for number of illuminants 1, Other socket, Housing material steel, Housing color white, Type of voltage AC/DC, Rated voltage 220 ... 240V, LED -Rated current at constant current 116 ... 126mA, control gear LED control gear, current-controlled, with control gear, DALI dimming, light distributor diffuser lens/optics/panel, reflector without, light distribution asymmetrical, light emission direct, beam angle narrow beam 11-20°, rated service life L70/ B50 at 25 °C 70000h, rated service life L80/B50 at 25 °C 50000h, rated service life L90/B50 at 25 °C 25000h, degree of protection (IP) IP20, protection class I, glow wire test according to IEC 60695-2-11 650 °C - 30 s , Max. system power 27.5W, rated luminous flux according to IEC 62722-2-1 4000lm, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, power factor 0.9, width 63mm, height/depth 50mm, length 1478mm, Type of Wiring termination, 5 poles, conductor cross-section 0.5mm², connection type other, customers from industry and retail are looking for general lighting solutions that pay for themselves in a reasonable time and that meet all relevant standards for supermarkets and industrial applications. Maxos LED is associated with limited investment costs, allows considerable energy savings (up to 55% compared to fluorescent lamp systems with LLCG) due to the high efficiency of up to 133 Im/W and at the same time achieves the required illuminance with the required color rendering and glare control. The minimalist Maxos LED light carrier , in which a wide or narrow beam lens optic is integrated, can be easily integrated into existing mounting rails of the Maxos continuous-row lighting system. Maxos LED is also available with a double asymmetrical optic, which is ideal for use in retail aisles. There are two versions regarding the lumen package. Firstly, the variant (LED40S) with 4,000 luminaire lumens, which can be u

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

