×



Item Number EB13301724

https://www.eibabo.uk/rzb/emergency-light-spotlight-led-28w-106grd-emergency-luminaire-23w-ip65-672088.1131.1-eb13301724



Emergency light spotlight LED 28W 106Grd - Emergency luminaire 23W IP65 672088.1131.1

RZB

672088.1131.1 4051859027607 EAN/GTIN

214,20 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Emergency lamp Spotlight LED 4000K 106° 672088.1131.1 Type of mounting Surface-mounted/recessed, Function of escape route lighting, Suitable for marking type other, Type of marking not applicable, Monitoring device without, Switching type maintained/standby mode, Central feed (central battery), Battery properties other, Light source LED not replaceable, With lamp, suitable for number of lamps 1, socket without, number of lamp heads 1, housing material aluminium, housing color anthracite, cover material glass transparent, type of voltage AC/DC, nominal voltage 220 ... 240V, control gear LED control gear current-controlled, light distributor reflector, Energy efficiency class of the permanently installed lamp A++, A+, A (LED), protection class (IP) IP65, protection class (NEMA) other, impact resistance IK07, protection class I, luminaire with limited surface temperature "D mark", rated ambient temperature according to IEC62722-2-125 ... 25°C, max. system power 23W, Rated luminous flux according to IEC 62722-2-1 2300Im, luminous flux in standby mode 2300Im, color temperature 4000 ... 4000K, power factor 0.95, width 109mm, height/depth 226mm, length 194mm, type of wiring termination, number of poles 3, conductor cross-section 2.5mm², connection type plug-in connection, Made in Germany. 3 different light distributions: Narrow Spot, Medium Spot and Flood. Stationary installation or mobile with plug and 5 m connecting cable. Seawater resistant coating optionally available. Central battery emergency light option available. Second cable inlet for looping through. Reduced connected load with the same luminous flux of the switchable version to save energy. Dali version with increased luminous flux. COB LEDs with interchangeable socket, optionally light color 830 or 840. LED service life 50,000 h (L80, B10). Pole and wall mounting accessories available. Suitable for use in the food and beverage industry. Safety light for central supply in maintained mode. Corrosion-resistant die-cast aluminum housing for outdoor use. Brack

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE
Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

