

Item Number EB11600057

https://www.eibabo.uk/maico/fan-ventilator-for-in-house-bathrooms-er-60-f-eb11600057

Fan - Ventilator for in-house bathrooms ER 60 F

×



Maico **FR 60 F** 0084.0102 4012799841029 EAN/GTIN

190,24 GBP excl. VAT** plus shipping



14-16 days* (GBR)

Fan ER 60 F nominal width 75mm, volume flow 62m³/h, color white, medium temperature -20 ... 40°C, flush-mounted installation type, rated voltage 230V, mains frequency 50Hz, combination with delayed twilight switch, nominal current 0.16A, speed 12501/min, material of the housing plastic, direction axial, protection class (IP) other, width 250mm, height 260mm, depth 150mm, version with light control: Barrier-free product because it switches on/off automatically. The light control switches the fan on at a minimum brightness in the room, e.g. B. when switching on a lamp. Switch-on brightness (on the device) min. 30 lux. Switch-off brightness (on the device) max. 0.3 lux. There is no need to install a switch. Switch-on delay approx. 50 seconds. Follow-up time approx. 6 minutes. Not speed controllable. Circuit variant: With an additional switch, the fan can be switched off independently of the room lighting (see circuit diagrams on the Internet). Fan with cover and G2 filter for installation in flush-mounted housing. For oneroom or two-room ventilation with a single fan (exception: version H and GVZC EC). Electrical plug connection for quick installation of the fan in the housing. Hassle-free filter changes without tools. Cover can be rotated by +- 5°, making it possible to compensate if the housing is inserted crookedly. Easy-to-install snap fastening of the fan in the housing. Color traffic white, similar to RAL 9016. All MAICO ER devices comply with protection class IP X5 and can therefore be installed in area 1 according to DIN VDE 0100-701, even with water jets. For details see planning information. Protection class II. The extremely steep characteristic curve shows the high pressure capacity of the ER fans. Robust energy-saving capacitor motor. ER 60 GVZC EC: with energy-saving EC motor. Motor with thermal overload protection. Maintenance-free, with ball bearings closed on both sides. Volume flow characteristic curve and leakage air rate tested by TÜV Bayern eV Leakage air volume flow < 0.01 m3/h. Shaft level difference according to DIN 4109, tested by IAB Oberursel. With VDE mark. Article: ER 60 F, version: light control, delivery volume: 62 m3/h, speed: 1250 1/min, air direction: ventilation, speed controllable: no, SEC average: -19.38 kWh/(m2*a), voltage type: alternating current , Rated voltage: 230 V, mains frequency: 50 Hz, power consumption: 21 W, IMax: 0.16 A, protection class: IP, Material: plastic, color: traffic white, similar to RAL 9016, weight: 1.5 kg, filter class: G2, blow-out direction: sideways, width: 250 mm, height: 260 mm, depth: 150 mm, conveyor temperature at IMax: 40 °C , follow-up...

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

