×



Item Number EB11600802

https://www.eibabo.uk/maico/axial-in-line-fan-three-phase-dn-300-duct-fan-3230m3-h-dzr-30-2-b-eb11 600802



Axial in-line fan, three-phase DN 300 - Duct fan 3230m³/h DZR 30/2 B

ZR 30/2 B

MaicoDZR 30/2 B
0086.0025
4012799860259 EAN/GTIN

829,03 GBP excl. VAT**

plus **shipping**



14-16 days* (GBR)

Axial pipe fan three-phase DN 300 DZR 30/2 B Material of the housing stainless steel, air volume unloaded 3230m3/h, connection voltage 400V, protection class (IP) IP55, length 300mm, diameter of the housing 380mm, pipe sleeve made of galvanized sheet steel, with flange on both sides. 8-blade impellers made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Flange holes in accordance with DIN EN 12220:1998. DZR 56/6 B and DZR 56/4 B: Flange holes according to DIN EN 12220:1998. To avoid vibration transmission to the pipe system: Use elastic connecting pieces, feet and vibration dampers High protection class IP 55. Exception EZR/DZR... D IP 54. Installation possible in any position. Motor: asynchronous motor, speed controllable. Exception: Type DZR 40/2 B. Not suitable for conveying water vapor saturated air. The conveying direction is marked on the device with a direction of rotation and conveying direction arrow. Reversing operation: The volume flow decreases by approx. 35% if the conveying direction is abnormal. Three-phase motor: DZR series. Rated voltage 400 V, 50 Hz. Thermal overload protection as standard. Exception: Available on request for DZR 25/4 D and pole-changing axial tube fans. The connections are potential-free on terminals and must be connected to a full motor protection switch, e.g. MV 25, or the control circuit of a contactor. Pole-changing fans: Ensure overload protection with a full motor protection switch to be provided on site. Electrical connection: External terminal box with cable grommets. Safety instructions: The fan may only be put into operation if protection against contact with the impeller is guaranteed in accordance with DIN EN ISO 13857. Article: DZR 30/2 B, delivery volume: 3670 m3/h, nominal delivery volume: 2650 m3/h / in opt Efficiency, pressure pfs, nominal: 168 Pa - in opt. Efficiency, speed nnominal: 2865 1/min - in opt. Efficiency, impeller type: axial, speed controllable: yes, reversibility: yes, voltage type: three-phase current, rated voltage: 400 V, mains frequency: 50 Hz, nominal power: 360 W / in opt. Efficiency, Irated: 0.8 A / in opt. Efficiency, IMax: 1 A, protection class: IP 55, thermal class: B, pole-changing: no, power supply cable: 7 / 1.5 mm2, installation position: horizontal / vertical, material: sheet steel, galvanized, weight: 12.65 kg, nominal width: 300 mm, width: 380 mm, height: 424 mm, depth: 300 mm, conveyor temperature at nominal current: 60 °C, conveyor temperature at IMax: -20 °C to 60 °C, overall efficiency e: 49.3%, measurement category: D ,...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME
Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

