

https://www.eibabo.uk/maico/exhaust-system-fan-insert-ventilator-for-in-house-bathrooms-er-60-gvz-eb11600771



## Exhaust system fan insert - Ventilator for in-house bathrooms ER 60 GVZ

×

**Maico** ER 60 GVZ 0084.0107 4012799841074 EAN/GTIN

154,77 GBP excl. VAT\*\* plus shipping



14-16 days\* (GBR)

Exhaust air system flush-mounted fan insert ER 60 GVZ nominal width 75mm, volume flow 62m3/h, color white, medium temperature -20 ... 40°C, mounting type flushmounted, rated voltage 230V, mains frequency 50Hz, composition other, nominal current 0.12A, speed 8501/min, material of the housing plastic, direction axial, protection class (IP) other, width 250mm, height 250mm, depth 150mm, version with base load circuit and delay timer: The device runs in continuous operation at 35 m3/h. Switching to full load with a switch-on delay of approx. 50 seconds. Full load follow-up time approx. 6 minutes. Not speed controllable. Circuit variant: The base load can be switched on or off with an additional switch (see circuit diagrams on the Internet). Fan with cover and G2 filter for installation in flush-mounted housing. For one-room or two-room ventilation with a single fan (exception: version H and GVZC EC). Electrical plug connection for quick installation of the fan in the housing. Hassle-free filter changes without tools. Cover can be rotated by +- 5°, making it possible to compensate if the housing is inserted crookedly. Easy-to-install snap fastening of the fan in the housing. Color traffic white, similar to RAL 9016. All MAICO ER devices comply with protection class IP X5 and can therefore be installed in area 1 according to DIN VDE 0100-701, even with water jets. For details see planning information. Protection class II. The extremely steep characteristic curve shows the high pressure capacity of the ER fans. Robust energy-saving capacitor motor. ER 60 GVZC EC: with energy-saving EC motor. Motor with thermal overload protection. Maintenance-free, with ball bearings closed on both sides. Volume flow characteristic curve and leakage air rate tested by TÜV Bayern eV Leakage air volume flow < 0.01 m3/h. Shaft level difference according to DIN 4109, tested by IAB Oberursel. With VDE mark. Article: ER 60 GVZ, version: base load and delay timer, delivery volume: 35 m3/h / 62 m3/h, speed: 850 1/min / 1250 1/min, air direction: ventilation, speed controllable: no, SEC average: -3 .43 kWh/(m2\*a), voltage type: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, power consumption: 10 W / 21 W, IMax: 0.12 A / 0.16 A, protection class: IP X5, mains supply cable : 5 / 1.5 mm2, installation location: wall / ceiling, installation type: flush-mounted, system type: decentralized, material: plastic, color: traffic white, similar to RAL 9016, weight: 1.5 kg, filter class: G2, blow-out direction: sideways, width: 250 mm, height: 250 mm, depth: 150 mm, conveyor temperature at IMax: 40 °C, follow-up time: 6 min, switch-on...

## YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



**COMPLAINTS HANDLING**Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<a href="www.eibmarkt.de">www.eibmarkt.de</a>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

