×



Item Number EB11600776

https://www.eibabo.uk/maico/exhaust-air-system-surface-mounted-fan-ventilator-for-in-house-bathrooms-er-ap-60-h-eb11600776



Exhaust air system surface-mounted fan - Ventilator for in-house bathrooms ER-AP 60 H

Maico

ER-AP 60 H 0084.0154 4012799841548 EAN/GTIN

373,73 GBP excl. VAT**

plus shipping



14-16 days* (GBR)

Exhaust air system surface-mounted fan ER-AP 60 H nominal width 75mm, volume flow 61m³/h, color white, medium temperature -20... 40°C, mounting type surface-mounted, rated voltage 230V, mains frequency 50Hz, composition other, nominal current 0.13A, speed 9001/min, Material of the housing plastic, direction axial, protection class (IP) other, width 236mm, height 236mm, depth 217.5mm, version with humidity control and base load switching: Barrier-free product as it switches on/off automatically. Switch-on point: 60%, 70%, 80% or 90% relative humidity adjustable with jumper. Switch-off point: approx. 10% below the switch-on point (always a fixed value). Not speed controllable. Not suitable for second room ventilation. Manual operation possible via a switch, e.g. B. Switching on full load using the light switch. Standard circuit: Fan runs in base load operation, humidity control is active, full load operation when the switch-on point is exceeded, base load operation when the switch-off point is undershot. Further switching variants: fan operation with or without base load operation, manual switching on of full load, switching the fan on or off using a switch. Switching on the full load using the light switch and associated follow-up control (run-on time 6 minutes) of the fan. The fan always runs until the humidity in the room has fallen below the switch-off humidity, regardless of the circuit variant. Surface-mounted fan with G2 filter for ventilation of bathrooms, toilets or kitchens. With maintenance-free fire protection metal butterfly valve to prevent fire spread K90-18017. Housing can be rotated, thereby connecting the outlet nozzle to the top left or top right to the main line. Color traffic white similar to RAL 9016. Easy filter change without tools. Metal outlet nozzle DN 75/80 with metal butterfly valve with automatic release device. The extremely steep characteristic curve shows the high pressure capacity of the ER fans. Robust energy-saving capacitor motor. Maintenance-free, with ball bearings closed on both sides. Electrical plug connection for quick installation of the fan in the housing. All MAICO ER devices comply with protection class IP X5 and can therefore be installed in area 1 according to DIN VDE 0100-701, even with water jets. For details see planning information. Protection class II. General building authority approval, approval number: Z-51.1-45. Approval notices on request or on our homepage Volume flow characteristic and leakage air rate tested by TÜV Bayern eV Leakage air volume flow < 0.01 m3/h. Shaft level difference according to DIN 4109, tested by IAB Oberursel, With VDE...

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



COMPLAINTS HANDLINGObliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500.000 customers worldwide



25 YEARS OF EXPERIENCE In worldwide mail order



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT
With order history



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

- ** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.
- *** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

