



**Window fan 260mm, automatic - Window ventilator
490m³/h 225mm EVN 22**



Maico
EVN 22
0080.0855
4012799808558 EAN/GTIN

419,40 GBP excl. VAT**
plus shipping



3-5 days* (GBR)

Window fan 260mm, automatic EVN 22, mains frequency 50Hz, rated voltage 230V, medium temperature -20... 40°C, housing material plastic, color white, volume flow 490m³/h, speed 11601/min, protection class (IP) IP24, ventilation version, nominal width 225mm, automatic closing flap, housing, base plate, inlet nozzle and rain cover made of galvanized sheet steel. Galvanized protective grille on the outlet side, contact protection in accordance with DIN EN ISO 13857. Stable transport eyes enable transport by crane. 8-blade impeller made of glass fiber reinforced polyamide. Dynamically balanced in 2 levels, in accordance with quality level 6.3, DIN ISO 1940, Part 1. Can be switched over for ventilation or ventilation (exception EZD... E). Conveying direction: The following figure shows the conveying direction: Standard conveying direction: Blowing over the motor. Reversing operation: Suction via the motor. Reversing operation (exception EZD... E): The volume flow decreases by approx. 35% if the conveying direction is abnormal. Motor: asynchronous motor. Reversible. Exception: Fans with shaded-pole motors (.../E). Thermal overload protection as standard. Three-phase motor: DZD series. Rated voltage 400 V, 50 Hz. Protection class DZD... D IP 54. Protection class DZD... B and... E IP 55. Electrical connection: connection cable, approx. 1.7 m long. Safety instructions: The fan may only be put into operation if contact protection of the impeller is guaranteed in accordance with DIN EN ISO 13857. Article: DZD 25/4 D, delivery volume: 800 m³/h, speed: 1425 1/min, impeller type: axial, Speed controllable: yes, reversible: yes, voltage type: three-phase current, rated voltage: 400 V, mains frequency: 50 Hz, nominal power: 50 W, IMax: 0.14 A, protection class: IP 54, thermal class: B, mains supply cable: 5 / 1.5 mm² location: roof, installation position: vertical, material: sheet steel, galvanized, weight: 11.5 kg, nominal width: 250 mm, width: 570 mm, height: 570 mm, depth: 325 mm, conveyor temperature at nominal current: -20 °C up to 60 °C, conveyor temperature at IMax: -20 °C to 60 °C

YOUR ADVANTAGES



WORLDWIDE TRADE
Corporate video eibmarkt®



99% CUSTOMER SATISFACTION
> 500,000 customers worldwide



DHL TRACK & TRACE
Shipment tracking



COMPLAINTS HANDLING
Obliging and 100% safely



25 YEARS OF EXPERIENCE
In worldwide mail order



ORDER LIVE CHAT
With order history



SHORT DELIVERY TIME
Warehousing



REFUND
Within 14 days



DATA PROTECTION
Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

