

Item Number EB11605289

https://www.eibabo.uk/maico/centrifugal-roof-fan-dn-250-roof-mounted-ventilator-825m3-h-148w-ehd-2 5-eb11605289



Centrifugal roof fan DN 250 - Roof mounted ventilator 825m3/h 148W EHD 25

×

Maico **EHD 25** 0087.0305

4012799873051 EAN/GTIN

521,57 GBP excl. VAT**

plus shipping



14-16 days* (GBR)

Centrifugal roof fan DN 250 EHD 25 Mains frequency 50Hz, rated voltage 230V, housing material sheet steel, volume flow 825m³/h, nominal power 148W, air flow temperature -20 ... 50°C, protection class (IP) IPX5, nominal diameter 250mm, corrosion protection galvanized, space-saving roof fan with extremely small dimensions. For venting. Elegant housing made of galvanized and powder-coated sheet steel. Aluminum cover. The cover is easily removable for cleaning work. Coated access protection grille. Centrifugal impeller with backward curved blades. Degree of protection IP X5. Motor: Outrunner condenser motor. Operating capacitor ready for connection in the terminal box. Speed controllable. Thermal overload protection as standard. Robust motor with ball bearings, maintenance-free. Installation instructions: Thanks to its low weight, no crane or goods lift is required to transport the EHD to the roof. Electrical connection: Connection to terminal block in the housing. Safety instructions: With free intake, the fan may only be put into operation if protection against accidental contact with the impeller is guaranteed in accordance with DIN EN ISO 13857. Item: EHD 25, delivery volume: 825 m3/h, impeller type: radial, speed controllable: yes, reversible: no, energy efficiency class: C, type of voltage: alternating current, rated voltage: 230 V, mains frequency: 50 Hz, rated power: 148 W, IMax: 0 .65 A, degree of protection: IP X5, mains cable: 3 / 1.5 mm2, installation location: roof, installation position: vertical, material: sheet steel, galvanized, weight: 8 kg, nominal diameter: 250 mm, width: 405 mm, height: 405 mm, depth: 302 mm, conveying medium temperature at IMax: -20 °C to 50 °C, sound pressure level: 55 dB(A) / distance 3 m, free field conditions

YOUR ADVANTAGES



WORLDWIDE TRADE Corporate video eibmarkt®



COMPLAINTS HANDLING Obliging and 100% safely



SHORT DELIVERY TIME Warehousing



99% CUSTOMER SATISFACTION > 500,000 customers worldwide



25 YEARS OF EXPERIENCE



REFUND Within 14 days



DHL TRACK & TRACE Shipment tracking



ORDER LIVE CHAT With order history



DATA PROTECTION Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

