



Miniature circuit breaker 1-p C6A S401M-C6


ABB

S401M-C6

2CCS571001R0064

7612270101382 EAN/GTIN

32,15 GBP excl. VAT**
plus shipping



14-16 days* (GBR)

Circuit breaker 6A C 1p S401M-C6 tripping characteristic C, number of poles (total) 1, number of fused poles 1, rated current 6A, rated voltage 400V, rated insulation voltage Ui 440V, rated impulse withstand voltage Uimp 4kV, rated switching capacity Icn according to EN 60898 at 230 V 10kA, rated switching capacity Icn according to EN 60898 at 400 V 10kA, rated switching capacity Icu according to IEC 60947-2 at 230 V 25kA, rated switching capacity Icu according to IEC 60947-2 at 400 V 10kA, type of voltage AC, frequency 50 ... 50Hz, energy limitation class 3, overvoltage category 3, degree of pollution 3, additional equipment possible, width in pitch units 1, installation depth 75mm, degree of protection (IP) IP20, ambient temperature during operation -25 ... 55°C, connectable conductor cross-section solid 0.8 ... 25mm², the S 400 series circuit breakers protect cables and lines against overload and short circuit according to DIN VDE 0100-430 and DIN VDE 0100-530. They meet the building regulations DIN VDE 0641-11 or IEC/EN 60898-1, DIN VDE 0660-101 or IEC/EN60947-2. Its patented connection terminal ensures simple and safe contacting and handling by means of a pressure plate. Conductor cross-sections up to 35 mm² can be connected directly to the device via the connection terminal with insulation in protection class IP20. Contact is made directly via the socket system and the outer conductor contact can be freely selected (L1, L2 or L3). The extensive range of accessories offers you everything you need for your installation tasks. Numerous approvals make the S 400 fit for worldwide use. Before delivery, each device is subjected to three intensive tests for quality and performance.

YOUR ADVANTAGES


WORLDWIDE TRADE

Corporate video eibmarkt®


99% CUSTOMER SATISFACTION

> 500,000 customers worldwide


DHL TRACK & TRACE

Shipment tracking


COMPLAINTS HANDLING

Obliging and 100% safely


25 YEARS OF EXPERIENCE

In worldwide mail order


ORDER LIVE CHAT

With order history


SHORT DELIVERY TIME

Warehousing


REFUND

Within 14 days


DATA PROTECTION

Guarantee

© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (www.eibmarkt.de). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

eibabo® the Smart Home technology shop
eibabo® electronics cheap online order
eibabo® electric appliances buy online

