

Item Number EB17108151

×

https://www.eibabo.uk/tcs/video-front-door-station-2-buttons-1-row.ap-si-door-station-door-communicat ion-2-button-avc1102...-eb17108151



Video front-door station 2 buttons 1-row.AP si - Door station door communication 2-button AVC1102...

TCS AVC11020-0010 4035138028431 EAN/GTIN

564,92 GBP excl. VAT**

plus shipping



Video front-door station 2 buttons 1-row.AP si AVC11020-0010 Installation technology bus system, surface-mounted installation, number of call buttons 2, with cover, protection against vandalism, with camera, material aluminium, color silver, height 175mm, width 104mm, depth 16mm, TCS video front-door station for surface mounting, AVC11020-0010 with 2 bell buttons, item number: AVC11020-0010, image / VIDEO PROPERTIES, color camera with CCD sensor, day/night switching: automatic, infrared lighting for close-range illumination, diagonal detection angle: 90 degrees, Resolution: 380 TVL, focal length: f = 3.6 mm, light sensitivity: 0.2 lux, device properties, video outdoor station, number of bell buttons: 2, mounting type: surface mounting, housing type: surface mounting, integrated loudspeaker, housing material: aluminum, housing color : natural anodised, bell button material: metal with maintenance-free contacts, shatterproof nameplate glass, sensor-controlled nameplate lighting, opening principle: win:clip, volume ke voice output: adjustable, volume of microphone sensitivity: adjustable, extended features, light switch function: on unprogrammed bell button, name field: white backlit, number of wires: 6-wire required, installation mix audio, video, access to a system: possible, commissioning and configuration: manual, with service device, system configuration memory: permanently integrated, technical data, technology: 2-wire TCS:BUS, current consumption, at rest: in 6-wire operation i(a) = 0.14 mA, I(P) = 50 mA, current consumption , maximum: i(Pmax) = 50 mA, surface-mounted housing HxWxD mm: 175x104x16, camera field HxW mm: 36x72, name plate HxW mm: 24x68, information plate HxW mm: 32x68, recommended mounting height: 1.6 m, permissible ambient temperature: -20 to + 50 degrees C, UV resistance: unrestricted, scope of delivery, for changing the name badges: win:clip key, for labeling: name badges

YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

** Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

*** Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online

