

Item Number EB11549615

19.04.2024/16:10

×

https://www.eibabo.uk/philips-licht/led-light-carrier-581led55s-840psdwbwh-gear-tray-for-light-line-syst em-4mx850-66124499-eb11549615

## LED light carrier 581LED55S/840PSDWBWH - Gear tray for light-line system 4MX850 #66124499

Philips Licht 4MX850 #66124499 66124499 4030732661244 EAN/GTIN

114,01 GBP excl. VAT\*\*

plus shipping bulky item



LED light carrier 581LED55S/840PSDWBWH 4MX850 66124499 Light source LED not interchangeable, With light source, Suitable for number of light sources 1, Other socket, Housing material steel, Housing color white, Type of voltage AC/DC, Rated voltage 220 ... 240V, LED rated current at constant current 153 ... 167mA, control gear LED control gear, current-controlled, with control gear, DALI dimming, light distributor diffuser lens/optics/panel, reflector without, light distribution symmetrical, light emission direct, beam angle wide beam 41-80°, rated service life L70/B50 at 25° C 70000h, rated service life L80/B50 at 25° C 50000h, rated service life L90/B50 at 25° C 25000h, degree of protection (IP) IP20, protection class I, glow wire test according to IEC 60695-2-11 650°C - 30 s, max. system performance 36.3W, rated luminous flux according to IEC 60722-2-1 5500Im, light color white, color temperature 4000 ... 4000K, color rendering index CRI 80-89, power factor 0.9, width 63mm, height/depth 50mm, length 1528mm, type of Wiring termination, 5 poles, conductor cross-section 0.5mm², connection type other, customers from industry and retail are looking for general lighting solutions that pay for themselves in a reasonable time and that meet all relevant standards for supermarkets and industrial applications. Maxos LED is associated with limited investment costs, allows considerable energy savings (up to 55% compared to fluorescent lamp systems with LLCG) due to the high efficiency of up to 133 Im/W and at the same time achieves the required illuminance with the required color rendering and glare control. The minimalist Maxos LED is also available with a double asymmetrical optic, which is ideal for use in retail aisles. There are two versions regarding the lumen package. Firstly, the variant (LED40S) with 4,000 luminaire lumens, which can be used as a direct 1:1 replacement for existing light sources with a 1x58 W or 1x49 W fluorescent lamp and reflector. There is also an LED light carrier with 5,500 and 6,600 lumens

## YOUR ADVANTAGES



© 1997-2024 eibmarkt.com GmbH - Kemmlerstrasse 1 - 08527 Plauen - Germany

eibabo® and eibmarkt® are registered trademarks of EIBMARKT® GmbH holding company (<u>www.eibmarkt.de</u>). eibabo® is a company of eibmarkt.com GmbH. eibmarkt.com GmbH is a 100% subsidiary of EIBMARKT® GmbH holding.

\* Note on delivery time: Day = Monday to Friday, no public holiday in Bavaria or Saxony. Goods are also delivered on Saturdays (DHL).

\*\* Payment methods may vary from country to country. All prices plus shipping and excluding customs duties or other additional costs (import sales tax) for deliveries outside the EU.

\*\*\* Savings compared to RRP = the manufacturer's recommended retail price. RRP is the price recommended to retailers by the manufacturer, importer or wholesaler as a resale price to the customer. The RRP is also referred to as the list price and is defined as the highest possible price that a buyer would pay for a specific product before any discounts (Source of gross list prices: Germany).

> eibabo® the Smart Home technology shop eibabo® electronics cheap online order eibabo® electric appliances buy online



